



# NANNI QMS12M60 SILENT MARINE GENERATOR 12KW 60 HZ EPA TIER III

## Product description:

NANNI QMS12M60 SILENT MARINE GENERATOR 12KW 60 HZ EPA TIER III

NANNI QMS12M60 is a single phase marine generator equipped with a Kubota EPA Tier III, 4-stroke diesel engine capable of delivering a maximum power of 12KW at 60Hz.

The NANNI QMS12M60 is equipped with a Kubota EPA tier III certified base engine used for years in marine and industrial applications worldwide.

The NANNI QMS12M60 generator is equipped with a fast-heating injector and glow plug and are located in the combustion chamber, ensuring that the engine will start even at low temperatures.

The cooling system allows the NANNI QMS12M60 to operate at an optimal temperature. In the case of closed-loop heat exchanger cooling, the coolant is cooled by seawater flowing through the heat exchanger.

The NANNI QMS12M60 is equipped with a closed-loop heat exchanger.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS12M60 is improved, resulting in low fuel consumption.

NANNI QMS12M60 is complete with fresh and salt water exchanger and anti-noise cabin making it super quiet.

## TECHNICAL FEATURES NANNI QMS12M60

Phase Type: Single Phase

Maximum Power: 12 KVA / 12 KW

Continuous Use Power: 10.7 KVA / 10.7 KW

Fuel: Diesel





Voltage: 120 - 240 V  
Frequency: 60 Hz  
Engine: Kubota, 4-stroke  
Emission Standard: EPA tier III  
Engine Revs. 1800  
Boosting: Electric  
Consumption: 4 Lt/h at full load  
Length: 1050 mm  
Width: 540 mm  
Height: 710 mm  
Weight: 291 Kg

Are you looking for a marine power generator with different technical features? Here you can find the full range of NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

**Product features:**

Phase: Single phase  
Maximum power single phase (KW): 12  
Continuous power single phase (KW): 10.7  
Maximum power single phase (KVA): 12  
Continuous power single phase (KVA): 10.7  
Fuel: Diesel  
Frequency (Hz): 60  
Voltage (V): 120 / 240  
Engine: Kubota, 4 stroke  
Emissions Regulations: EPA tier III  
Engine rpm (rpm): 1800  
Starting system: Electric  
Number cylinders: 4  
Cylinders' position: In line  
Cooling: Water  
Inyección : Indirect (E-TVCS)  
Alternator: Electronic regulator  
Consumption (L/h): 4 at 100% of the load  
Length (mm): 1050  
Width (mm): 540  
Height (mm): 710  
Dry weight (Kg): 291  
Silenced: Yes



