



MOSA GE 7000 HBM-L SINGLE PHASE STAGE V GENERATOR 6,7KVA AVR

Product price:

1.612,17 € tax excluded

Product description:

MOSA GE 7000 HBM-L STAGE V SINGLE-PHASE GENERATOR 6,7KVA AVR

The MOSA GE7000HBM-L single-phase generator, is equipped with a Honda GX 390 Stage V gasoline-powered engine, and is complete with AVR voltage regulator.

MOSA GE7000HBM-L is equipped with electric start and has a low fuel consumption, in fact it consumes only 2.4 liters/hour at 75% of the load for an autonomy of up to 8.5 hours of operation. Extremely practical sockets and controls make starting and operating the generator easy and quick.

The MOSA GE7000HBM-L generator features an engine support system with a durable steel frame and rubber shock absorbers. These shock absorbers, located on either side of the engine and angled at a 45° angle, significantly reduce engine vibration from an already quiet machine. Aesthetically beautiful, functionally effective.

The front panel of the MOSA GE7000HBM-L is configured as follows:

- Engine ON-OFF switch
- Fuel tap
- Air control
- Fuel level indicator
- Hour meter
- Voltmeter
- Thermomagnetic circuit breaker
- Thermomagnetic circuit breaker for 230V/16A socket(s) (N°2 for version with SCHUKO sockets)
- Output sockets
- Earth terminal (PE)





VOLTAGE REGULATOR AVR

The MOSA GE7000HBM-L Generator is supplied with AVR voltage regulator. The AVR is a device that allows to **keep the output more constant and less dependent on the load**. Thanks to the AVR there are fewer drops or spikes in current and this makes it safer to use the various devices connected, improving performance and durability.

MOSA GE7000HBM-L TECHNICAL SPECIFICATIONS

Phase Type: Single Phase
Continuous Use Power: 6.0 KVA / 5.4 KW
Maximum Power: 6.7 KVA / 6.0 KW
Motor: HONDA GX 390
Motor RPM: 3000 rpm
Emission Standard: Stage V
Boosting: Manual with self-winder
Fuel: Gasoline
Voltage: 230 V
Frequency: 50 Hz
Voltage controller: AVR
Tank capacity: 20 l
Run time at 75% load: 8.5 h
Consumption at 75% load: 2.4 Lt/h
Acoustic power: 97 dB(A) (72 dB(A) @ 7m)
Length: 520 mm
Width: 770 mm
Height: 630 mm
Dry weight: 81 kg

Are you looking for a generator with different technical characteristics? Here you can find the area dedicated to MOSA generators or other specialized brands.

Images and technical data not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 6
Continuous power single phase (KW): 5.4
Maximum power single phase (KVA): 6.7
Continuous power single phase (KVA): 6
Fuel: Gasoline
Frequency (Hz): 50





Voltage (V): 230
Engine: Honda GX390
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Speed governor: Mechanical
Starting system: Pull starter with recoil
Engine capacity (cm³): 389
Number cylinders: 1
Oil capacity (L): 1.1
Cooling: Air
Alternator: Synchronous self-excited, self-regulated, brushless
Bore x stroke (mm): 88 x 64
Fuel tank capacity (L): 20
Consumption (L/h): 2.4 at 75% of the load
Running time (h): 8.5 at 75% of the load
Acoustic pressure: 72 dB(A) at 7 m
Length (mm): 520
Width (mm): 770
Height (mm): 630
Dry weight (Kg): 81
ATS Switch device : No
Voltage regulator: AVR