



GREEN POWER GP 8000XM/KE SINGLE- PHASE GENERATOR STAGE V ELECTRIC START 7,7KVA

Product price:

1.235,00 € tax excluded

Product description:

GREEN POWER GP 8000XM/KE SINGLE-PHASE GENERATOR STAGEV 7,7KVA

The generator GREENPOWER GP 8000XM/KE single-phase is equipped with a KOHLER CH 440 **StageV** gasoline-supplied engine, and is complete with capacitor voltage regulator (**AVR optional**).

GREENPOWER GP 8000XM/KE is equipped with electric start and has a low fuel consumption, in fact it consumes only 2.3 liters/hour at 75% load for a range of up to 3 hours of operation. Extremely practical sockets and controls make starting and operating the generator easy and quick.

The generator is compact and convenient to maneuver and transport thanks to its compact size, its weight of 96 kg as well as the practical tubular handles. In addition, it is equipped with a practical and convenient start system, so that it can be put into operation quickly and easily.

The GREENPOWER GP 8000XM/KE generator is equipped with KOHLER CH 440 StageV engine that allows this machine to deliver a maximum single-phase power of 7.7KVA.

STAGEV EMISSION STANDARD

The acronym STAGEV defines the guidelines and limits of gas emissions from engines. The regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to function correctly is that the genset works at its design temperature.





The electrical control panel of the GREENPOWER GP 8000XM/KE generator is composed of:

- Output sockets: 1x 230V 32A CEE / 1x 230V 16A SCHUKO
- Thermal circuit breaker
- Voltmeter

TECHNICAL FEATURES GREENPOWER GP 8000 XM/KE

Phase Type: SinglePhase

Continuous Use Power: 7 KVA / 7 KW

Maximum Power: 7.7 KVA / 7.7 KW

Motor: KOHLER CH 440

Motor RPM: 3000 rpm

Emissions Standard: StageV

Start: Electric

Fuel: Gasoline

Voltage: 230 V

Frequency: 50 Hz

Socket panel: 1 x Schuko 16A 230V / 1 x CEE 32A 230V

Tank capacity: 7 l

Run time at 75% load: 3.0 h

Consumption at 75% load: 2.3 Lt/h

Length: 780 mm

Width: 570 mm

Height: 680 mm

Dry weight: 96 Kg

Are you looking for a generator with different technical characteristics? Here you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data not binding.

Product features:

Phase: Single phase

Maximum power single phase (KW): 7.7

Continuous power single phase (KW): 7

Maximum power single phase (KVA): 7.7

Continuous power single phase (KVA): 7

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x Schuko 16A 230V / 1 x CEE 32A 230V





Engine: Kohler CH 440
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Elettrico
Engine capacity (cm³): 429
Number cylinders: 1
Cooling: Air
Alternator: LINZ E1C10 MI
Poles: 2
Fuel tank capacity (L): 7
Consumption (L/h): 2.3 al 75% del carico
Running time (h): 3 al 75% del carico
Length (mm): 780
Width (mm): 570
Height (mm): 680
Dry weight (Kg): 96
Silenced: No
Super silenced: No
Product type: Generator
ATS Switch device : No
Voltage regulator: Capacitor / AVR (optional)
Engine manufacturer: Kohler