



# GREEN POWER GP 4000XM/YE SINGLE- PHASE GENERATOR ELECTRIC START DIESEL STAGEV 3,5KVA

Product price:

**1.885,00 € tax excluded**

## Product description:

GREENPOWER GP 4000XM/YE SINGLE-PHASE GENERATOR ELECTRIC START DIESEL STAGEV 3,5KVA

The generator GREENPOWER GP 4000XM/YE single-phase, is equipped with a YANMAR L70AE **StageV** Diesel-supplied engine, complete with capacitor voltage regulator (**AVR optional**).

GREENPOWER GP 4000XM/YE is equipped with electric start and has a low fuel consumption, in fact it consumes only 1,2 liter/hour at 75% of load for a range of up to 3 hours of operation.

The generator provides reliable power for home, work and recreational environments, safely appliances and other electronic devices. Extremely convenient sockets and controls make starting and operating the generator easy and fast.

The GREENPOWER GP 4000XM/YE generator has a convenient double-curved handle for easy mobility and storage, has a completely steel structure and a tank with a maximum capacity of 3,5 liters. The generator guarantees an efficient and silent operation thanks to the YANMAR L70AE StageV engine with electric start, which can deliver a maximum power of 3.5KVA.

## STAGEV EMISSION STANDARDS

The acronym STAGEV defines the guidelines and limits of gas emissions from engines. The regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to work correctly is that the genset works at its design temperature.





---

## TECHNICAL FEATURES GREENPOWER GP 4000XM/YE

Phase Type: Single-phase  
Continuous Duty: 3.1 KVA / 3.1 KW  
Maximum Power: 3.5 KVA / 3.5 KW  
Engine: YANMAR L70AE  
Engine RPM: 3000 rpm  
Emission Regulation: Stage V  
Starting: Electric  
Fuel: Diesel  
Voltage: 230 V  
Frequency: 50 Hz  
Socket panel: 2 x Schuko 16A 230V  
Tank capacity: 3,5 l  
Autonomy at 75% load: 3 h  
Consumption at 75% load: 1,2 Lt/h  
Length: 780 mm  
Width: 570 mm  
Height: 680 mm  
Dry weight: 80 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data are not binding.

### Product features:

Phase: Single phase  
Maximum power single phase (KW): 3.5  
Continuous power single phase (KW): 3.1  
Maximum power single phase (KVA): 3.5  
Continuous power single phase (KVA): 3.1  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 2 x 230V 16A SCHUKO  
Engine: Yanmar L70AE, 4 stroke  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 296  
Number cylinders: 1





Cooling: Air

Alternator: LINZ SP10 SE

Poles: 2

Fuel tank capacity (L): 3.5

Consumption (L/h):

Running time (h): 3 al 75% del carico

Length (mm): 780

Width (mm): 570

Height (mm): 680

Dry weight (Kg): 80

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: Capacitor / AVR (optional)

Engine manufacturer: Yanmar