



GENSET MG 70 SS-I GENERATOR 66KVA SILENCED SINGLE- PHASE / THREE-PHASE AVR

Product price:

25.952,00 € tax excluded

Product description:

GENSET MG 70 SS-I GENERATOR 66KVA SILENCED SINGLE/ THREE-PHASE AVR

The GENSET MG 70 SS-I single/three-phase generator is equipped with an FPT F34 Diesel engine, capable of delivering a power of 66 KVA complete with AVR voltage regulator.

This generator set is equipped with electric start, manual with 12V battery, and is equipped with COMAP LITE 9 control unit which allows you to view all the electrical parameters of the engine, of the functions, status of the generator, manage the entire group and view, in case they occur, the errors or alarms of the system.

The GENSET MG 70 SS-I is equipped with a soundproof cabin, thanks to which there is a drastic reduction of noise pollution up to 69 dB recorded at a distance of 7 meters, thanks to these characteristics the group can be considered super silenced .

The GENSET MG 70 SS-I guarantees efficient and silent operation thanks to the FPT F34 engine, which allows to deliver a maximum power of 66KVA. In addition, this generator set is equipped with electric or automatic starting via the ATS panel, which allows it to be switched on automatically in the event of a blackout.

AUTOMATIC TRANSFER SWITCH ATS

The GENSET MG 70 SS-I unit is designed for the use of an ATS automatic transfer switch. Thanks to which you will no longer have to worry about blackouts because if it goes off the





power grid this panel is able to automatically start the GENSET MG 70 SS-I and will allow you to continue your business without losing your work data.

TECHNICAL FEATURES GENSET MG 70 SS-I:

Type of phase: Singlephase / Threephase

Continuous use singlephase power: 20 KVA / 16 KW

Maximum singlephase power: 22 KVA / 17.6 KW

Continuous use threephase power: 60 KVA / 48 KW

Threephase maximum power: 66 KVA / 52.8 KW

Engine: FPT F34

Engine revs: 1500 rpm

Emissions regulations: Stage V

Starting: Electric

Fuel: Diesel

Voltage available at terminals: 230/400 V

Frequency: 50 Hz

Voltage regulator: AVR

Socket panel: 1 x CEE 400V 32A / 1 x CEE 400V 16A / 1 x CEE 230V 32A / 2 x CEE 230V 16A

Tank capacity: 195 lt

Consumption at 80% of the load: 11 Lt / h

Acoustic pressure: 94 (69 dB a 7 mt)

Length: 2400 mm

Width: 950 mm

Height: 1675 mm

Dry weight: 1270 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to GENSET generators or other specialized brands.

Non-binding images and technical data.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 17.6

Continuous power single phase (KW): 16

Maximum power single phase (KVA): 22

Continuous power single phase (KVA): 20

Maximum power three phase (KW): 52.8

Continuous power three phase (KW): 48





Maximum power three phase (KVA): 66

Continuous power three phase (KVA): 60

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x CEE 400V 32A / 1 x CEE 400V 16A / 1 x CEE 230V 32A / 2 x CEE 230V 16A

Engine: FPT F34

Emissions Regulations: Stage 5

Engine rpm (rpm): 1500

Starting system: Electric

Engine capacity (cm³): 3400

Number cylinders: 4

Fuel tank capacity (L): 195

Consumption (L/h): 11 at 80% load

Running time (h): 19 at 80% load

Length (mm): 2400

Width (mm): 950

Height (mm): 1675

Dry weight (Kg): 1270

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

