



BADA TMS80E ELECTRIC PANTOGRAPH LIFTING PALLET TRUCK IN 100% STAINLESS STEEL

Product price:

5.841,00 € tax excluded

Product description:

BADA TMS80E ELECTRIC PANTOGRAPH LIFTING PALLET TRUCK IN 100% STAINLESS STEEL 1000Kg

The BADA TMS80E transpallet in AISI 304 stainless steel is equipped with electric pantograph lifting up to 800 mm, designed to position goods at the ideal height and reduce the operator's effort during the picking and depositing of the goods.

Thanks to its construction characteristics, and the construction entirely in **AISI 304 stainless steel**, the pallet truck can be used in the food, chemical and pharmaceutical industries.

BADA TMS80E is resistant, easy to handle and with an ergonomic design, it fully responds to the most stringent hygienic requirements as it can be sanitized with regular high pressure washing.

BADA TMS80E is a transpallet built entirely in AISI 304 stainless steel (including the lifting pump and hydraulic components), suitable for use in humid and corrosive environments where impeccable cleaning and hygiene are required and solving corrosion problems linked by the use of acids and saline solutions. The bearings are waterproof and the bushings are made of polyamide material as required by the food industry.

This model **ON EXPLICIT REQUEST OF THE CUSTOMER** can be supplied in AISI 316 stainless steel (**Optional WITH surcharge**).

TECHNICAL CHARACTERISTICS BADA TMS80E

Type of propulsion: Manual

Drive system: Manual

Lifting: Electric





Construction material: AISI 304 stainless steel

Capacity: 1000 Kg

Quantity of rear wheels : 2

Quantity front wheels: 2

Teflon side stabilizing rollers

Lifting height: 115/800 mm

Fork width: 170 mm

Fork length: 1150 mm

Turning radius: 1450 mm

Drawbar height at rest: 1190 mm

Total length: 1750 mm

Total width: 550 mm

Net weight: 149 Kg

Are you looking for a pallet truck with different technical characteristics? [HERE](#) you can find the area dedicated to BADA or other Transpallet specialized brands.

Images and technical data are not binding.

Product features:

Drive: Manual

Operator type: Manuale

Load capacity (Kg): 1000

Service weight (Kg): 149

Tyres: front wheels: Nylon/Polyurethane

Tyres: rear wheels: Nylon/Polyurethane

Quantity rear wheels: 2

Quantity front wheels: 2

Rear balancing axle: No

Lift height (mm): 800

Height of tiller in drive position max (mm): 1190

Height lowered (mm): 95

Overall lenght (mm): 1750

Overall width (mm): 550

Thickness fork (mm): 45

Width fork (mm): 170

Lenght fork (mm): 1150

Distance between fork arms (mm): 210

Turning radius (mm): 1450

Weigher: No

Type of lifting: Electric

