



GENERATOR SINGLE-PHASE / THREE-PHASE STAGEV 19,2KVA AVR

Product price:

6.810,00 € tax excluded

Product description:

GENERATOR SINGLE-PHASE / THREE-PHASE STAGEV 19,2KVA AVR

Generator single-phase / three-phase of 19,2 KVA with BRIGGS & STRATTON engine powered by STAGEV Gasoline at 3000 rpm, compact and easy to use.

The generator consists of an NSM Made in Italy, self-excited brushless alternator with **AVR** voltage regulator. The generator is equipped with electric start with battery that allows a practical and fast use even when cold. The generator has a low fuel consumption, in fact it consumes only 6,5 liters/hour at 75% of the load.

The generator is not supplied with feet as these are supplied separately.

The generator is part of the QUIET series because thanks to the hood has low noise emissions and is supersilenced. This generator is 3000 RPM, with BRIGGS & STRATTON engine with electric start with key and battery.

STAGEV EMISSIONS REGULATION

The generator is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

TECHNICAL FEATURES

Phase Type: Single-phase / Three-phase

Singlephase Continuous Power: 5.8 KVA / 4.6 KW

Singlephase Maximum Power: 6.4 KVA / 5.1 KW

Threephase Continuous Power: 17.5 KVA / 14 KW





Threephase Maximum Power: 19.2 KVA / 15.3 KW
Power Factor cos fi?: 0. 8
VAC voltage: 230 / 400 V
Frequency (Hz): 50
Voltage regulator: AVR
Start framework: Manual / Automatic
Engine: BRIGGS & STRATTON 31HP
RPM: 3000
Power supply: Gasoline
Emissions standard: STAGE V
Fuel tank capacity: 60 l
Fuel consumption @ 75 % load: 6.5 l/h
Autonomy @ 75 % load: 9.2 h
Sound pressure: 72 dB(A) @ 7m
Length: 1200 mm
Width: 730 mm
Height: 930 mm
Net weight: 280 Kg

Manual electric panel with:
n. 1 CEE 16A 3P 230V socket
n. 1 CEE 32A 5P 400V socket
General switch
connector for ATS
hour counter

Discover the full range of current generator on our catalog to find the one that best suits your needs.

Pictures and technical data not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 5.1
Continuous power single phase (KW): 4.6
Maximum power single phase (KVA): 6.4
Continuous power single phase (KVA): 5.6
Maximum power three phase (KW): 15.3
Continuous power three phase (KW): 14
Maximum power three phase (KVA): 19.2
Continuous power three phase (KVA): 17.5
Fuel: Gasoline





Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x 230V 16A 3P CEE - 1 x 400V 32A 5P
Engine: BRIGGS & STRATTON 31HP
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Manual / Automatic
Engine capacity (cm³): 896
Number cylinders: 2
Cooling: Air
Alternator: NSM, made in Italy
Fuel tank capacity (L): 60
Consumption (L/h): 6.5 @ 75 % del carico
Running time (h): 9.2 @ 75 % del carico
Length (mm): 1200
Width (mm): 730
Height (mm): 930
Dry weight (Kg): 280
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Briggs&Stratton
Video: MKDdx7hAnHc

