



EMACH EMG R3000 GENERATOR 2,9KW SINGLE-PHASE AVR STAGEV

Product price:

312,00 € tax excluded

Product description:

EMACH EMG R3000 GENERATOR 2,9KW SINGLE-PHASE AVR STAGEV

EMACH EMG R3000 is a single-phase generator, equipped with a gasoline-powered R210 **StageV** engine, delivering a maximum power of 2,9KW, complete with AVR voltage regulator.

EMACH EMG R3000 is equipped with **tear-off with self-wrapping**, equipped with an AVR regulator that allows connection with sensitive electronic devices (computers, smartphones, TVs) without the risk of damaging them due to sudden changes in the supply current.

The EMACH EMG R3000 provides reliable power for home, business and leisure environments, safely powers home appliances and other electronic devices. Extremely practical sockets and controls make starting and operating the generator easier, making these operations extremely simple and fast.

EMACH EMG R3000 is supplied complete with a handling trolley, to facilitate mobility and storage. EMACH EMG R3000 has a steel structure and a tank with a maximum capacity of 15 liters which allows the generator to run for about 6 hours at full load.

AVR VOLTAGE REGULATOR

The Generator is supplied complete with AVR voltage regulator. The AVR is a device that allows you to **keep the output more constant and less dependent on the load**. Thanks to the AVR there are fewer current drops or peaks and this makes the use of the various connected devices safer, improving their performance and duration.

STAGEV EMISSIONS REGULATION





The generator is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

Technical characteristics EMACH EMG R3000

Type of phase: Single-phase
Continuous power: 2.7 KVA / 2.7 KW
Maximum power: 2.9 KVA / 2.9 KW
VAC voltage: 230 V
Frequency (Hz): 50
Voltage regulator: AVR
Starting panel: Recoil
Engine: R210 4-stroke
Emissions standard: StageV
Revolutions per minute: 3000 rpm
Power supply: Petrol
Sockets panel: 2 x shuko 16 A
Tank capacity: 15 l
Autonomy: 6 h
Consumption: 2.5 l / h
Acoustic pressure: 72 dB (A) @ 7 m
Length: 615 mm
Width: 500 mm
Height: 480 mm
Net weight: 41 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to EMACH generators or other specialized brands

Images and technical data are not binding and may be subject to revisions.

Product features:

Phase: Single phase
Maximum power single phase (KW): 2.9
Continuous power single phase (KW): 2.7
Maximum power single phase (KVA): 2.9
Continuous power single phase (KVA): 2.7
Fuel: Gasoline
Frequency (Hz): 50





Voltage (V): 230
Sockets configuration: 2 x 220V 16A SCHUKO
Engine: R210 4-stroke
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Ignition: Recoil
Starting system: Pull starter
Cooling: Air
Fuel tank capacity (L): 15
Consumption (L/h): 2.5
Running time (h): 6
Acoustic pressure: 72 dB(A) at 7 m
Length (mm): 615
Width (mm): 500
Height (mm): 480
Dry weight (Kg): 41
Silenced: No
Super silenced: No
ATS Switch device : No
Voltage regulator: AVR