



EMACH EMG R5500 GENERATOR SINGLE PHASE 5KW AVR STAGEV

Product price:

578,00 € tax excluded

Product description:

EMACH EMG R5500 SINGLE-PHASE GENERATOR 5KW STAGEV

EMACH EMG R5500 is a single-phase generator, equipped with a gasoline engine R390 **StageV**, delivering a maximum power of 5,4KW, complete with AVR voltage regulator.

EMACH EMG R5500 is equipped with **tear-off with self-wrapping**, equipped with an AVR regulator that allows connection with sensitive electronic devices (computers, smartphones, TVs) without the risk of damaging them due to sudden changes in the supply current.

The EMACH EMG R5500 provides reliable power for home, business and leisure environments, safely powers home appliances and other electronic devices. Extremely practical sockets and controls make starting and operating the generator easier, making these operations extremely simple and fast.

AVR VOLTAGE REGULATOR

The EMACH EMG R5500 is supplied complete with AVR. The AVR is a device that allows you to **keep the output more constant and less dependent on the load**. Thanks to the AVR there are fewer current drops or peaks and this makes the use of the various connected devices safer, improving their performance and duration.

STAGEV EMISSIONS REGULATION

The generator is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard





engines.

Technical characteristics EMACH EMG R5500

Type of phase: Single-phase

Continuous power: 5 KVA / 5 KW

Maximum power: 5.4 KVA / 5.4 KW

VAC voltage: 230 V

Frequency (Hz): 50

Voltage regulator: AVR

Starting panel: Recoil

Engine: R390 4-stroke

Emissions standard: Stage V

Revolutions per minute: 3000 rpm

Fuel: Gasoline

Sockets panel: 1 x shuko 16A / 1 x 230V 32A

Tank capacity: 25 l

Autonomy: 7 h

Consumption: 3.57 l / h

Acoustic pressure: 85 dB (A) @ 7 m

Length: 720 mm

Width: 550 mm

Height: 580 mm

Net weight: 90 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to EMACH generators or other specialized brands

Images and technical data are not binding and may be subject to revisions.

Product features:

Phase: Single phase

Maximum power single phase (KW): 5.4

Continuous power single phase (KW): 5

Maximum power single phase (KVA): 5.4

Continuous power single phase (KVA): 5

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 220V 32A 2P+T CE - 1 x 220V 16A SCHUKO

Engine: R390 4-stroke

Emissions Regulations: Stage 5





Engine rpm (rpm): 3000
Ignition: Recoil
Starting system: Pull starter
Cooling: Air
Fuel tank capacity (L): 25
Consumption (L/h): 3.5 at 100% of the load
Running time (h): 7 at 100% load
Acoustic pressure: 85 dB(A) at 7 m
Length (mm): 720
Width (mm): 550
Height (mm): 580
Dry weight (Kg): 90
Silenced: No
Super silenced: No
ATS Switch device : No
Voltage regulator: AVR