



# GENERATOR SINGLE-PHASE 9,7KVA SILENT ELECTRIC START

**Product price:**

**7.290,00 € tax excluded**

## **Product description:**

### GENERATOR SINGLE-PHASE 9,7KVA ELECTRIC START

The generator single-phase, is equipped with a KOHLER 425-2 Diesel-supplied engine, complete with capacitor voltage regulator (**AVR optional**).

It is equipped with electric start and has a low fuel consumption, in fact it consumes only 2,5 liters/hour at 75% of the load for an autonomy of up to 8 hours of operation.

The generator is equipped with silenced casing that can be opened in two sections made of sheet 20/10, soundproofing material in class 1, internal muffler. Thanks to these devices, the generator can be considered super-silenced, with a noise emission of only 75 dB recorded at a distance of 7 meters from the source.

The generator guarantees efficient and silent operation thanks to the KOHLER KD 15440 engine, which allows to deliver a maximum power of 9.7KVA.

### ATS AUTOMATIC STARTING FRAME

The generator is designed for use with an ATS automatic start-up panel. Thanks to this, you will no longer have to worry about blackouts, in the event of a power failure this panel is able to automatically turn on the generator and allow you to continue your business.

The generator control panel consists of:

- Thermomagnetic circuit breaker and isolation control
- Sockets: 1 x 16A 3P 230V / 1 x 32A 3P 230V
- ATS arrangement
- Voltmeter
- Ammeter





- Hour meter
- Ignition switch
- Emergency stop button

## TECHNICAL FEATURES

Phase Type: Single Phase  
Continuous Use output: 8.8 KVA / 8.8 KW  
Maximum output: 9.7 KVA / 9.7 KW  
Motor: KOHLER 425-2  
Motor Speed: 3000 rpm  
Emissions Standard: NOT Emitted  
Boosting: Electric  
Fuel: Diesel  
Voltage: 230 V  
Frequency: 50 Hz  
Socket Frame: 1 x 16A 3P 230V / 1 x 32A 3P 230V  
Tank Capacity: 20 l  
Autonomy at 75% of load: 8 h  
Consumption at 75% of load: 2.5 Lt/h  
Acoustic pressure: 75 dB(A) @ 7 m  
Length: 940 mm  
Width: 650 mm  
Height: 840 mm  
Dry weight: 235 Kg

Are you looking for a generator with different technical characteristics? Here you can find the area dedicated to generators or other specialized brands.

Images and technical data not binding.

### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 9.7  
Continuous power single phase (KW): 8.8  
Maximum power single phase (KVA): 9.7  
Continuous power single phase (KVA): 8.8  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 1 x 16A 3P 230V / 1 x 32A 3P 230V  
Engine: Kohler KD 425/2





Emissions Regulations: Stationary Use  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 954  
Number cylinders: 2  
Cooling: Air  
Alternator: LINZ E1C11MB  
Poles: 2  
Fuel tank capacity (L): 20  
Consumption (L/h): 2.5 at 75% of the load  
Running time (h): 8 at 75% load  
Acoustic pressure: 75 dB(A) at 7 m  
Length (mm): 940  
Width (mm): 650  
Height (mm): 840  
Dry weight (Kg): 235  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : Optional  
Voltage regulator: Capacitor / AVR (optional)  
Engine manufacturer: Kohler

