



---

# PRAMAC P4000 Generator

## Single-phase 3.5kVA

### STAGEV

**Product price:**

**2.629,00 € tax excluded**

#### **Product description:**

PRAMAC P4000 SINGLE-PHASE GENERATOR 3.5 KVA STAGE V

The PRAMAC P4000 single-phase generator with Yanmar L70V STAGE V diesel engine delivers 3.5 KVA of power and comes with capacitor voltage regulation (optional AVR).

The generator adapts perfectly to a wide range of uses thanks to the transport kit, which allows safe and easy relocation. With its enlarged 18 L tank, this generator offers an outstanding runtime of 15 h at 75% load.

These generators feature high-quality components, are lightweight and compact, easy to use, and boast a modern design with practical electric start.

The PRAMAC P4000 generator is equipped with electric start or automatic start via an ATS panel, enabling automatic start-up in the event of a blackout.

#### **STAGE V EMISSIONS STANDARD**

The generator set is equipped with a “mobile” STAGE V engine, as required by European Regulation 2016/1628. These new engines exponentially reduce particulate and nitrogen oxide emissions released into the environment, ensuring a 200% reduction in environmental impact compared to standard engines.

#### **AUTOMATIC TRANSFER SWITCH (ATS) START PANEL (OPTIONAL)**

The generator set is prearranged for use with an Automatic Transfer Switch (ATS) panel. Thanks to this, you no longer need to worry about blackouts: if the mains power fails, the panel can automatically start the generator so you can continue your activities without losing work data.

#### **TECHNICAL FEATURES PRAMAC P4000 Single-Phase Generator 3.5kVA:**

Phase type: Single-phase





Continuous power: 3.24 KVA / 2.92 KW  
Maximum power: 3.57 KVA / 3.21 KW  
Engine: Yanmar L70V  
Engine speed: 3000 rpm  
Emissions standard: STAGE V  
Starting: Electric  
Fuel: Diesel  
Voltage: 230 V  
Frequency: 50 Hz  
Voltage regulation: Capacitor (optional AVR)  
Socket panel: 1 x SCHUKO 230V 16A | 1 x CEE 230V 16A | 1 x CEE 230V 32A  
Tank capacity: 18 L  
Autonomy: 15.25 h at 75% load  
Consumption: 1.18 L/h at 75% load  
Sound pressure level: 68 dB(A) @ 7 m  
Length: 800 mm  
Width: 525 mm  
Height: 850 mm  
Dry weight: 132 kg

Looking for a generator set with different technical features? [HERE](#) you can find the section dedicated to PRAMAC generator sets and other specialized brands.

**Product features:**

Phase: Single phase  
Maximum power single phase (KW): 3.2  
Continuous power single phase (KW): 2.9  
Maximum power single phase (KVA): 3.5  
Continuous power single phase (KVA): 3.2  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 1 X SCHUKO 230V 16A | 1 X CEE 230V 16A | 1 X CEE 230V 32A  
Engine: Yanmar L70V, 4 stroke  
Engine rpm (rpm): 3000  
Speed governor: Mechanical  
Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 320  
Oil capacity (L): 1.01  
Cooling: Air  
Alternator: Brushless  
Poles: 2





Fuel tank capacity (L): 18  
Consumption (L/h): 1.18 at 75% load  
Running time (h): 15.25 at 75% load  
Acoustic power: 96 dB(A)  
Acoustic pressure: 68 dB(A) at 7 m  
Length (mm): 800  
Width (mm): 525  
Height (mm): 850  
Dry weight (Kg): 132  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : Optional  
Voltage regulator: Capacitor / AVR (optional)  
Engine manufacturer: Yanmar

