



GENERATOR SINGLE PHASE / THREE PHASE SILENCED VEHICULAR 19,1KVA STAGEV

Product price:

13.510,00 € tax excluded

Product description:

GENERATOR SINGLE PHASE / THREE PHASE SILENCED VEHICULAR 19,1KVA STAGEV

Generator single-phase / three-phase silenced vehicular is equipped with a diesel-powered Yanmar 4TNV88 STAGEV engine, capable of delivering a maximum power of 19,1KVA at 1500 rpm.

Compact, light and silent vehicle generator designed for installation on board special vehicles such as workshop wagons, motorhomes, trucks and caravans, emergency vehicles of the Civil Protection.

The vehicular generator is equipped with a soundproofing cabin that makes it super silenced, with a sound emission of 55dB (A) at a distance of 7 m. The painted aluminum soundproof booth is extremely light and highly resistant to external agents.

This vehicle generator is equipped with a ComAp InteliNano control unit that allows you to control and verify all the main functions of the unit and, if necessary, it will report any failure or error in the operation of the machine.

STAGEV EMISSIONS REGULATION

This vehicle generator is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

TECHNICAL FEATURES





Phase type: Single-phase / Three-phase
Maximum single-phase power: 6,3KVA / 5 KW
Maximum three-phase power: 19,1 KVA / 15.3 KW
Fuel: Diesel
Voltage : 230 / 400V
Frequency: 50 Hz
Starting: Electric
Cooling: Water
Engine: Yanmar 4TNV88
Emissions standard: STAGEV
Mechanical power: 24.1 Hp
Number of cylinders: 4
Displacement: 2190 cc
Engine rpm: 1500 rpm
Fuel consumption: 3.5 l / h
Acoustic pressure: 62 dB (A) @ 7 m
Alternator: Synchronous
Length: 1570 mm
Width: 650 mm
Height: 810 mm
Weight: 550 Kg

Are you looking for a vehicle generator with different technical characteristics? [HERE](#) you can find the area dedicated to vehicle generators of specialized brands.

The images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 5
Maximum power single phase (KVA): 6.3
Maximum power three phase (KW): 15.3
Maximum power three phase (KVA): 19.1
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: Yanmar 4TNV88, 4 stroke
Engine rpm (rpm): 1500
Starting system: Electric
Engine capacity (cm³): 2190
Number cylinders: 4





Cooling: Water
Alternator: Synchronous
Protection degree: IP23
Motor insulation class: H
Consumption (L/h): 3.5 at 75% load
Acoustic power: 87 dB(A)
Acoustic pressure: 62 dB(A) at 7 m
Length (mm): 1570
Width (mm): 650
Height (mm): 810
Dry weight (Kg): 550
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : No
Voltage regulator: Compound
Engine manufacturer: Yanmar

