



GENERATOR 1,2KVA SINGLE PHASE STAGEV AVR

Product price:

175,00 € tax excluded

Product description:

GENERATOR 1,2KVA SINGLE PHASE STAGEV AVR

The generator single-phase is equipped with a STAGEV petrol engine, it is capable of delivering a maximum power of 1,2KVA, complete with AVR voltage regulator.

The generator is characterized by lower consumption and a longer life expectancy than the petrol-powered range. Equipped with a completely steel structure and a large metal tank with filling indicator. The generator guarantees efficient and silent operation thanks to the StageV petrol engine which allows to deliver a maximum power of 1.2 KVA.

STAGEV EMISSIONS REGULATION

The generator is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

AVR VOLTAGE REGULATOR

The purpose of the AVR in a power source is to keep the output stable. And if its operation is very simple when resistive loads are powered, the situation is more complex in the case of mainly inductive loads: the delayed phase current contrasts the inductor magnetic field, causing a drop in the alternator output terminals; to compensate for the phenomenon, the AVR intervenes automatically by increasing the excitation current, until the output returns to the nominal value. If the load is instead capacitive, the current acts as a magnetizer for the inductor causing an increase in the output voltage, and the AVR intervenes by reducing the excitation current

TECHNICAL FEATURES:





Phase type: Single phase
Continuous power: 1.1 KVA / 1.1 KW
Maximum power: 1.2 KVA / 1.2 KW
Fuel: Petrol
Voltage: 230 V
Frequency: 50 Hz
Engine: 4 HP
Engine rpm: 3000 rpm
Emissions standard: StageV
Starting: Manual pull
Voltage regulator: AVR
Consumption: 0.7 Lt / h at 75% of the load
Tank capacity: 7 Lt
Autonomy: 10 h at 75% of the load
Length: 475 mm
Width: 380 mm
Height: 380 mm
Weight: 24.7 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to specialized brands.

The images and technical data are not binding, the color of the group may vary based on availability.

Product features:

Phase: Single phase
Maximum power single phase (KW): 1.1
Continuous power single phase (KW): 1.2
Maximum power single phase (KVA): 1.1
Continuous power single phase (KVA): 1.2
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 Schuko + 12 V
Engine: 4 HP
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Manual recoil
Engine capacity (cm³): 113
Number cylinders: 1
Alternator: Synchronous self-excited, with brushes





Fuel tank capacity (L): 7

Consumption (L/h): 0,7 to 75% of the load

Running time (h): 10 to 75% of the load

Length (mm): 475

Width (mm): 380

Height (mm): 380

Dry weight (Kg): 24.7

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR