



GENERAC LT VTEVOQ LIGHT TOWER 4x320W G4 LED WITH GENERATOR 5KW STAGEV

Product description:

GENERAC LT VTEVOQ LIGHT TOWER 4x320W G4 LED WITH GENERATOR 5KW STAGEV

GENERAC LT VTEVOQ is a light tower equipped with four 320W Led floodlights that can be lifted up to a height of 7,5 m, capable of illuminating an area of 4500 m2.

The GENERAC LT VTEVOQ is equipped with a Kubota Z482 StageV Diesel engine, which in combination with the capacious 120 l tank manages to guarantee a working autonomy of 171 h. The GENERAC LT VTEVOQ has an extremely quiet operation, in fact it has a sound emission of only 63 dB(A) at 7m.

The Generac LT VTEVOQ, thanks to 4 LED floodlights can illuminate an area of 4500 square meters with a maximum luminous intensity of 188160 lm total. The light tower is equipped with a galvanized mast with a winch manual system that allows the floodlights to be raised to a maximum height of 7.5m. The winch is equipped with an anti-fall safety system that blocks its access and accidental release once positioned.

Ideal for lighting construction sites, parking lots, emergency sites, outdoor events, and other applications where intense, long-lasting illumination is needed in low light conditions.

TECHNICAL FEATURES GENERAC LT VTEVOQ

Lamp power: 4 x 320 W

Lamp type: LED

Total lumens: 188160 Lm

Illuminated area: 4500 m2

Lifting system: Manual

Pole rotation: 340°

Engine: Kubota Z482





Emission standard: StageV
Engine Cooling: Liquid
Cylinders (N): 2
Engine speed (50/60 Hz): 1500 / 1800 rpm
Alternator (kVA/V/Hz): 3.5/220/50 - 4.2/240/60
Electrical outlet (kVA/V/Hz): 2/220/50 - 2/240/60
Average sound pressure: 63 dB(A) @ 7m
Wind resistance: 80 km/h
Tank capacity: 120 l
Autonomy: 171 h
Minimum dimensions (W x D x H): 2480 x 1190 x 1950 mm
Maximum dimensions (W x D x H): 2480 x 2400 x 7500 mm
Dry weight: 620 kg

Are you looking for a product with different technical characteristics? HERE you can find the entire range of GENERAC lighting towers or other specialized brands.

Non-binding images and technical data.

Product features:

Phase: Single phase
Maximum power single phase (KW): 3.5
Maximum power single phase (KVA): 3.5
Fuel: Diesel
Voltage (V): 230
Engine: Kubota Z482
Emissions Regulations: Stage 5
Engine rpm (rpm): 1500 / 1800
Number cylinders: 2
Cooling: Coolant Liquid
Type of lamps: LED
Lamps: 4 x 320 W
Illuminated area (m²): 4500
Total lumens (Lm): 188160
Lifting System: Manual lifting system
Maximum height (m): 7.5
Mast rotation: 340°
Open size (mm): 2480 x 2400 x 7500
Closed size (mm): 2480 x 1190 x 1950
With generator / Without generator: With generator
Transportability: Stationary
Stability to wind (Km/h): 80 Km/h





Fuel tank capacity (L): 120

Running time (h): 171

Acoustic pressure: 63 dB(A) at 7 m

Dry weight (Kg): 620

Engine manufacturer: Kubota