



HONDA GX200 SXE5

Gasoline Engine 4.4 HP

Product description:

HONDA GX200 SXE5 Gasoline Engine 4.4 HP

HONDA GX200 SXE5 engines are recommended for a wide range of professional machines in the fields of construction, agricultural machinery, power generators, power welders, motor pumps, and other industrial applications.

TECHNICAL SPECIFICATIONS HONDA GX200 SXE5

Engine type: OHV horizontal shaft, eight cycle, 4-stroke

Number of cylinders: 1

Cylinder Arrangement: 25° inclined

Bore x stroke: 68 x 54 mm

Displacement: 196 cm³

Cooling: Forced air

Compression ratio: 8.5 : 1

Net power: 4.1 kW (5.5 HP) / 3 600 rpm

Continuous rated power 3000 rpm: 3.3 kW (4.4 HP)

Continuous rated power 3600 rpm: 3.7 kW (5.0 HP) / 3 600 rpm

Maximum torque: 12.4 Nm / 1.26 kgfm / 2 500 rpm

Ignition: Contactless transistor

Starting: Recoil with recoil starter

Fuel tank capacity: 3.1 liters

Fuel consumption at rated power: 1.7 Liters/hour - 3 600 rpm

Oil pan capacity: 0.6 Liters

Length: 313 mm

Width: 376 mm

Height: 346 mm

Net Weight: 16 kg

Looking for an engine with different technical characteristics? [HERE](#) you can find the area dedicated to HONDA engines or other specialized brands.





Images and technical data are not binding and may be subject to revision.

Product features:

Fuel: Gasoline

Engine: OHV horizontal shaft, eight cycle, 4-stroke

Ignition: A transistor contactless

Starting system: Manual

Engine capacity (cm³): 196

Number cylinders: 1

Cylinders' position: Inclined to 25°

Oil capacity (L): 0.6

Cooling: Forced air

Bore x stroke (mm): 68 x 54

Compression ratio: 8.5 : 1

Net power (kW): 4.1

Nominal power continuous: 3.3 KW (4.4 HP) / 3000 rpm - 3.7 KW (5.0 HP) / 3600 rpm

Maximum torque: 12.4 Nm / 1.26 kgfm / 2500 rpm

Fuel tank capacity (L): 3.1

Consumption (L/h): 1.7

Running time (h): 1.82

Length (mm): 321

Width (mm): 376

Height (mm): 346

Dry weight (Kg): 16.1

Engine manufacturer: Honda

