



GENERATOR 165KVA SUPER SILENCED SINGLE / THREE-PHASE AUTOMATIC PANEL

Product price:

23.105,00 € tax excluded

Product description:

GENERATOR 165KVA SUPER SILENCED SINGLE / THREE-PHASE AUTOMATIC PANEL

The generator single-phase/three-phase is equipped with a Perkins 1106A-70TAG2 Diesel engine, complete with an **AVR voltage regulator** and an automatic start control panel.

This generator is equipped with **electric start** with a 12V battery and features the **COMAP IL9 AMF 9** control panel that allows you to view all electrical parameters of the engine and generator, functions, generator status, fully manage the generator, and display any system errors or alarms if they occur.

The generator comes with a soundproofed canopy made of 20/10 thickness carbon steel, folded and welded, with an IP23 protection class and can be opened in two sections. This canopy allows the super silent generator to emit a sound pressure level of only 68 dB(A) @ 7 meters.

This generator **does not come with an oil collection tank**, but this device can be installed upon explicit request from the customer.

The generator ensures efficient and silent operation thanks to the Perkins 1106A-70TAG2 engine, which can deliver a maximum power of 165KVA. Additionally, this unit is equipped with electric start or automatic start through an ATS control panel, allowing for automatic startup in case of a blackout.

AUTOMATIC START CONTROL PANEL ATS (OPTIONAL)

The generator is designed for the use of an automatic start control panel ATS. With this panel, you no longer have to worry about blackouts because if the electrical grid fails, the control panel will automatically start the generator and allow you to continue your activities without losing your





work data.

TECHNICAL SPECIFICATIONS

Phase Type: Single-Phase / Three-Phase
Continuous Use Power: 150 KVA / 120 KW
Maximum Power: 165 KVA / 132 KW
Engine: Perkins 1106A-70TAG2
Engine Speed: 1500 rpm
Emission Standard: Non-emission
Start: Electric
Fuel: Diesel
Available Voltage at Terminals: 230 / 400 V
Frequency: 50 Hz
Voltage Regulator: AVR
Outlet Panel: Terminal Block
Tank Capacity: 170 l
Oil Collection Tank: NO
Autonomy at 75% Load: 6.9 h
Consumption at 75% Load: 24.7 Lt/h
Sound Pressure Level: 68 dB(A) @ 7 m
Length: 3300 mm
Width: 1100 mm
Height: 1770 mm
Dry Weight: 2050 Kg

Looking for a generator with different technical specifications? You can find a dedicated section for generators from specialized brands [HERE](#).

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power three phase (KW): 132
Continuous power three phase (KW): 120
Maximum power three phase (KVA): 165
Continuous power three phase (KVA): 150
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: Terminal box
Engine: Perkins 1106A-70TAG2





Emissions Regulations: Not Emitted

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 7010

Number cylinders: 6

Alternator: MECC ALTE ECP34-1L/4

Fuel tank capacity (L): 170

Consumption (L/h): 24.7 at 75% load

Running time (h): 6.9 at 75% load

Acoustic pressure: 68 dB(A) at 7 m

Length (mm): 3300

Width (mm): 1100

Height (mm): 1770

Dry weight (Kg): 2050

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Perkins

