



# VISA P9SG GENERATOR 10KVA SINGLE/THREE PHASE AVR

**Product price:**

**8.500,00 € tax excluded**

## **Product description:**

VISA P9SG GENERATOR 10KVA SINGLE/THREE PHASE AVR

The VISA P9SG single-phase/ three-phase Generator is equipped with Perkins 403A-11G1 Diesel engine, and is capable of delivering a maximum power of 10 KVA, complete with AVR voltage regulator.

The VISA P9SG is equipped with electric start, manual or automatic with 12V battery, and is equipped with Comap AMF 25 control unit that allows to display of all the electrical parameters of the engine and generator, functions, states of the genset, manage the genset entirely and display, in case they occur, the errors or alarms of the system.

The Visa P9SG generator is designed for easy operation and maintenance. It also features automatic start-up and shutdown functions to simplify daily use.

The robust and durable construction of the Visa P9SG ensures long service life and reliable performance over time. The high-quality motor provides steady power and low noise emission, reducing noise impact and making the generator suitable for use in noise-sensitive environments.

Thanks to the AVR voltage regulator included with the generator, the VISA P9SG is able to deliver "clean" current and voltage with an accuracy of less than one percent, this guarantees the user, to be able to safely connect any kind of electrical and electronic devices.

The VISA P9SG genset guarantees efficient and quiet operation thanks to the Perkins 403A-11G1 Engine motor, which allows it to deliver a maximum power of 10 KVA.

The Visa P9SG genset comes complete with:

- Differential Switch;
- Liquid collection tank with level sensor;





- Engine heater;
- Oil extraction pump

### ATS AUTHOMATIC TRANSFER SWITCH (OPTIONAL)

The generator is prepared for the use of Authomatic Transfer Switch ATS. Thanks to which you will no longer have to worry about blackouts because if the power grid goes out, this panel can automatically start the generator and allow you to continue your activity without losing your work data.

### TECHNICAL SPECIFICATIONS VISA P9SG

Phase Type: Single Phase / Three Phase  
Maximum power: 10 KVA / 8 KW  
Continuous power: 9 KVA / 7.2 KW  
Fuel: Diesel  
Voltage: 230 / 400 V  
Frequency: 50 Hz  
Engine: Perkins 403A-11G1  
Emission standard: Not Emitted  
Number of cylinders: 3  
Engine speed: 1500 rpm  
Starter: Electric  
Control unit: Comap AMF 25  
Voltage regulator: AVR  
Socket panel: Terminal block (Power socket)  
Tank capacity: 50 Lt  
Consumption: 2 Lt/h at 75% load  
Autonomy: 25 h at 75% load  
Length: 1802 mm  
Width: 752 mm  
Height: 1130 mm  
Net weight: 508 Kg

Are you looking for a generator set with different technical characteristics? [HERE](#) you can find the area dedicated to VISA generator sets or other specialized brands.

The images are purely indicative.

### Product features:

Phase: Single phase / Three phase  
Maximum power three phase (KW): 8





Continuous power three phase (KW): 7.2  
Maximum power three phase (KVA): 10  
Continuous power three phase (KVA): 9  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: Terminal box  
Engine: Perkins 403A-11G1  
Emissions Regulations: Not Emitted  
Engine rpm (rpm): 1500  
Starting system: Electric  
Number cylinders: 3  
Cooling: Water  
Alternator: STAMFORD S0L1-H  
Fuel tank capacity (L): 50  
Consumption (L/h): 2 at 75% of the load  
Running time (h): 25 at 75% of the load  
Length (mm): 1802  
Width (mm): 752  
Height (mm): 1130  
Dry weight (Kg): 508  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Perkins

