



# HYUNDAI LS 65003 GASOLINE GENERATOR SINGLE PHASE STAGE V AVR 6 KW

Product price:

**825,33 € tax excluded**

## Product description:

HYUNDAI LS 65003 GASOLINE GENERATOR SINGLE PHASE STAGE V AVR 6 KW

The HYUNDAI LS 65003 single/three phase generator, is equipped with a 4-stroke **StageV** engine supplied by gasoline, delivers a maximum power of 6KW, complete with AVR voltage regulator.

HYUNDAI LS 65003 is equipped with electric start with battery.

The HYUNDAI LS 65003 generator provides reliable power for home, work and leisure environments, safely appliances and other electronic devices. Extremely convenient sockets and controls make it easy to start and operate the generator, making these tasks extremely quick and easy.

The HYUNDAI LS 65003 generator has a convenient double-curved handle for easy mobility and storage. HYUNDAI LS 65003 has a completely steel structure and a tank with a maximum capacity of 25 lt.

## EMISSION STANDARD STAGEV

HYUNDAI LS 65003 is equipped with "mobile" STAGEV motorization, as required by European Regulation 2016/1628. These new engines make it possible to exponentially reduce the particulate and nitrogen oxide emissions delivered by the generator into the environment, and ensure a 200% reduction in environmental impact compared to standard engines.

## TECHNICAL CHARACTERISTICS HYUNDAI LS 65003

Phase type: Single-phase





Continuous use power: 5.5 KVA / 5.5 KW  
Maximum power 6 KVA / 6 KW  
Engine: 4-stroke  
Engine revolutions: 3000 rpm  
Emissions standard: StageV  
Starting: Electric  
Fuel: Gasoline  
Voltage: 230 V  
Frequency: 50Hz  
Socket panel: 1 x CEE 16A 230V / 1 x CEE 32A 230V  
Tank capacity: 25 l  
Sound pressure: 76 dB (A) @ 7 m  
Length: 860 mm  
Width: 600 mm  
Height: 620 mm  
Dry weight: 91 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to HYUNDAI generators or other specialized brands.

Images and technical data are not binding.

**Product features:**

Phase: Single phase  
Maximum power single phase (KW): 6  
Continuous power single phase (KW): 5.5  
Maximum power single phase (KVA): 6  
Continuous power single phase (KVA): 5.5  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 1 x CEE 16A 230V / 1 x CEE 32A 230V  
Engine: 4 Tempi  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Elettrico  
Alternator: Avvolgimento in rame  
Fuel tank capacity (L): 25  
Acoustic pressure: 76 dB(A) at 7 m  
Length (mm): 860  
Width (mm): 600  
Height (mm): 620





Shop name

---

Dry weight (Kg): 91

Silenced: Yes

Super silenced: No

ATS Switch device : No

Voltage regulator: AVR



PrestaShop