



GENERATOR SINGLE-PHASE 11KVA AVR STAGEV

Product price:

3.996,00 € tax excluded

Product description:

GENERATOR SINGLE-PHASE 11KVA AVR STAGEV

Generator single-phase equipped with a Honda GX 630 OHV (STAGE V) gasoline engine capable of delivering a maximum power output of 11KVA.

The generator also has low fuel consumption: only 5.5 liters/hour at 75% load. Thanks to the high quality and efficiency of its components, the generator is ideal for various types of work, from small hobby projects to large construction sites.

The generator is easy to install and operate, with clear and intuitive controls for easy starting and stopping. The generator is powered by a Honda GX 630 OHV gasoline engine **STAGE V**. These engines are highly reliable, ensuring efficient combustion and reduced fuel consumption. They are also equipped with a protection system that shuts down the engine if the oil level is too low.

The generator features a 29-liter tank with a large cap that is convenient to unscrew even while wearing work gloves. It has a fully steel structure and a large metal tank. The generator ensures efficient and quiet operation thanks to the Honda GX 630 OHV engine, which can deliver a maximum power output of 11 KVA.

The generator comes with:

- Automatic shutdown for low oil level
- 12V Battery
- 1 CEE 16A, 230V - 50 Hz single-phase socket
- 1 CEE 32A, 230V - 50 Hz single-phase socket
- Power output protections
- Differential switch
- Voltmeter
- Hour meter
- Central lifting hook





TECHNICAL SPECIFICATIONS

Phase Type: Single-Phase
Continuous Power: 10 KVA / 8 KW
Maximum Power: 11 KVA / 8.8 KW
Fuel: Gasoline
Voltage: 230 V
Frequency: 50 Hz
Engine: Honda GX 6300 OHV
Engine Speed: 3000 RPM
Emission Standards: Stage V
Startup: Electric
Voltage Regulator: AVR
Socket Configuration: 1 x 230V 16A CEE - 1 x 230V 32A CEE
Consumption: 5.5 l/h
Tank Capacity: 29 L
Autonomy: 5.27 h
Sound Pressure: 73 dB(A) at 7m
Length: 904 mm
Width: 507 mm
Height: 823 mm
Weight: 148 Kg

Looking for a power generator with different features? [HERE](#) you can find the area dedicated to generators from other brands specializing in the field.

Images and technical data are not binding and may be subject to revisions by the supplier.

Product features:

Phase: Single phase
Maximum power single phase (KW): 8.8
Continuous power single phase (KW): 8
Maximum power single phase (KVA): 11
Continuous power single phase (KVA): 10
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V 16A CEE - 1 x 230V 32A CEE
Engine: Honda GX630, 4 stroke, OHV
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric





Engine capacity (cm³): 688
Number cylinders: 2
Cooling: Air
Alternator: Synchronous
Protection degree: IP23
Motor insulation class: H
Fuel tank capacity (L): 29
Consumption (L/h): 5.5
Running time (h): 5.27
Acoustic power: 98 dB(A)
Acoustic pressure: 73 dB(A) at 7 m
Length (mm): 904
Width (mm): 507
Height (mm): 823
Dry weight (Kg): 148
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Honda