



PRAMAC OFF GRID LX LFP 60/100 PORTABLE BATTERY 100KW

Product description:

PRAMAC OFF GRID LX 60/100 LFP PORTABLE BATTERY 100KW

PRAMAC Off Grid LX LFP PORTABLE BATTERY: the ideal battery energy storage system for every need

PRAMAC Off Grid LX LFP is a universal energy storage system (BESS) ideal for a wide range of applications. It provides reliable energy in the most economical and environmentally friendly way, thanks to its innovative features and versatility.

Main features PRAMAC Off Grid LX LFP

PRAMAC Off Grid LFP lithium-ion deep cycle battery module: PRAMAC Off Grid LX LFP is a state-of-the-art technology that guarantees high energy density, long life and excellent safety.

Advanced control with touch screen display: Pramac Off Grid LX LFP is equipped with an intuitive control panel for quick and easy monitoring and performance management.

Remote monitoring via GSM can be monitored remotely via a dedicated app, allowing you to check performance anytime and from anywhere.

PRAMAC Off Grid PORTABLE BATTERY LX LFP Full system auto bypass: in the event of a system failure, power is automatically supplied from the grid or diesel generator.

PRAMAC off Grid Auto remote generator call: Pramac in the event of a power failure, the system can automatically call a diesel generator to restore power.

Technical Specifications PRAMAC Off Grid LX LFP:

Power output (continuous): 60 kVA





Peak power (5s): 120 kW

Voltage: 400/230 V

Frequency: 50 Hz

Phases: 3

Battery specifications

Battery (type): Li-Ion LFP

Nominal battery voltage: 48 V

Battery life (at 90% DoD): 6000 cycles

Nominal battery capacity (size): 96 kWh

AC-side usable energy (@90% DoD): 82 kWh

System throughput: 125 A

Length (L): 2240 mm

Width (W): 1160 mm

Height (H): 2018 mm

Weight: 2250 kg

Discharge temperature range: -10...45 °C

Charging temperature range: 0...45 °C

Instruments, controls and connections

Inverter protection: short circuit, overload, overtemperature

Discover the full range the entire range of PRAMAC off Grid storage systems or portable batteries or other specialized brands. Visit the dedicated section by clicking [HERE](#).

The images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Single phase / Three phase

Maximum power three phase (KW): 120

Continuous power three phase (KVA): 60

Frequency (Hz): 50

Voltage (V): 230 / 400

Battery type: Li-Ion NMC LFP

Length (mm): 1160

Width (mm): 1160

Height (mm): 2018

Battery voltage (V): 48

Weight (Kg): 2250

AC-side usable energy (@90% DoD): 82 kWh

Nominal battery capacity: 96 kWh





System passage capacity: 125 A

Discharge temperature range: -10...45 °C

Charging temperature range: 0...45 °C

