



MOSA GE8YSX 1WEEK WITH HEATER

Product price:

8.260,00 € tax excluded

Product description:

MOSA GE8YSX 1WEEK Generator with heater

MOSAGE8YSX single-phase 7,2 KW genset with diesel-powered Yanmar engine. The MOSA GE8 YSX genset has an electric starter. The alternator of the MOSA GE8 YSX genset is synchronous, single-phase, self-excited, self-regulated, brushless with class H insulation.

350-litre fuel tank: increases the genset's fuel autonomy to around 175 hours.

This MOSA GE8 YSX genset is compact and convenient to manoeuvre and transport thanks to its compact dimensions, its weight of 530 kg and its practical drilled base. Genset with enclosure to reduce noise emissions, making it supersilenced.

The MOSA GE8 YSX genset with 350-litre tank has a fuel consumption of 2 litres/hour at 75% load for an autonomy of more than 175 hours.

Sockets:

- 1x 230V 32A 3P+E CEE
- 1x 230V 16A 3P+E CEE
- 1x 230V 16A 2P+E Schuko

Technical specifications MOSA GE8 YSX:

- Maximum power single-phase: 7.2 KW
- Single-phase continuous use power: 6.7 KW
- Fuel: Diesel
- Voltage: 230 V
- Frequency: 50 Hz
- Engine: Yanmar 3TNV80
- Starting: Electric
- Acoustic power measured LwA: 87 dB(A) (62 dB(A) @ 7 m)
- Tank capacity: 350 l
- Consumption: 2 Lt/h at 75% of the load





Length: 1460 mm
Width: 700 mm
Height: 1550 mm
Weight: 530 Kg
Supersilenced
Heater: Yes

Features:

- Fully openable one-piece casing that facilitates all maintenance operations
- Rounded edges to allow rainwater runoff
- Recessed control panel can be closed by padlock, It houses the sockets and controls of the machine
- Central lifting hook
- Prepared for use with automatic EAS (AMF + ATS)
- Complies with EC directives for noise and safety

If you are looking for another product like the generator set MOSA GE8 YSX then you can see on our catalog other terrestrial generator sets.

Images and technical data are not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 7.2
Continuous power single phase (KW): 6.7
Maximum power single phase (KVA): 8
Continuous power single phase (KVA): 7.5
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V 32A 2P+T CEE - 1 x 230V 16A 2P+T CEE - 1 x 230V 16A 2P+T SCHUKO
Engine: Yanmar 3TNV80
Emissions Regulations: Stage 5
Engine rpm (rpm): 1500
Starting system: Electric
Engine capacity (cm³): 1200
Number cylinders: 3
Cooling: Water
Inyección : Indirect
Alternator: Synchronous self-excited, self-regulated, brushless
Fuel tank capacity (L): 350





Consumption (L/h): 2 at 75% of the load
Running time (h): 175 at 75% of the load
Length (mm): 1680
Width (mm): 770
Height (mm): 1550
Dry weight (Kg): 670
Product type: Generator
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Yanmar

