



PRAMAC GBW15P Generator Set Three-phase MCP 11.2KW Enclosure with manual control panel

Product price:

6.810,00 € tax excluded

Product description:

PRAMAC GBW15P THREE-PHASE MCP GENERATOR 11.2KW

PRAMAC GBW15P 11.2 kW three-phase generator with a diesel engine running at 1500 rpm. The PRAMAC GBW15P generator is equipped with an electric starter. The alternator of the PRAMAC GBW15P generator is a brushless, compound voltage regulator. The Perkins diesel engine makes the GBW15P generator very reliable, as it was built and designed using top-quality materials.

Thanks to its canopy, this generator is super-silenced. Furthermore, its compact size makes it easy to transport, install, and position, making this model ideal for power grid emergencies, construction, mobile workshops, and industrial applications. The PRAMAC GBW15P three-phase generator is suitable for outdoor use on construction sites or for small professional jobs outdoors.

Technical characteristics of the PRAMAC GBW15P MCP Three-Phase generator:

Maximum power Three-Phase: 11.28 KW - 14.10 kVA

Continuous use power Three-Phase: 10.18 KW - 12.72 kVA

Fuel: Diesel

Voltage: 400 V

Frequency: 50 Hz

Engine: Perkins 403D-15G

Starting: Electric

Consumption: 3.6 Lt/h at 100% of load

Length: 1645 mm

Width: 870 mm

Height: 1072 mm

Weight: 550 Kg

Compound

Exhaust gas emission level: Not regulated





Sockets:

N.1 3P+N+T CEE 400V 32A

N.1 3P+N+T CEE 400V 16A

N.2 2P+T CEE 230V 16A

N.1 230V 16A SCHUKO

The PRAMAC GBW15P generator is a professional diesel generator developed by Pramac with the features and equipment needed to obtain a top-class product. Superior. The PRAMAC GBW15P generator, with its low noise level, is the ideal generator for use in residential areas or during non-working hours. The GBW15P generator is equipped with a reliable diesel engine, top-quality components, and comprehensive instrumentation. If you are looking for a generator like the PRAMAC GBW15P THREE-PHASE generator, we recommend browsing our catalog of terrestrial generators to find the one that best suits your needs.

Product features:

Phase: Three phase

Maximum power three phase (KW): 11.28

Continuous power three phase (KW): 10.18

Maximum power three phase (KVA): 14.1

Continuous power three phase (KVA): 12.72

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Emissions Regulations: Stationary Use

Speed governor: Mechanical

Starting system: Elettrico

Engine capacity (cm³): 1496

Number cylinders: 3

Cylinders' position: In line

Oil capacity (L): 6

Cooling: Water

Alternator: Linz E1S13MD, with brushes

Poles: 4

Fuel tank capacity (L): 51

Consumption (L/h): 2.7 at 75% of the load / 3.6 at 100% of the load

Running time (h): 18.6 at 75% of the load / 14.2 at 100% of the load

Acoustic power: 95 dB(A)

Acoustic pressure: 66 dB(A) at 7 m

Length (mm): 1645



Width (mm): 870
Height (mm): 1072
Dry weight (Kg): 550
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : No
Voltage regulator: Compound
Engine manufacturer: Perkins