



PRAMAC GBW30P APERTO CON QUADRO COMANDO AUTOMATICO

Product description:

Motore Diesel. Raffreddamento ad acqua. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica. Quadro manuale MCP fornito di serie con 5 prese

Product features:

Phase: Three phase

Maximum power three phase (KW): 26

Continuous power three phase (KW): 24.4

Maximum power three phase (KVA): 32.5

Continuous power three phase (KVA): 30.5

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE

Engine: PERKINS 1103A-33G, naturally aspirated

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 3300

Number cylinders: 3

Cylinders' position: In line

Oil capacity (L): 8.3

Cooling: Water

Alternator: Mecc Alte ECP28-VL/4, brushless

Poles: 4

Fuel tank capacity (L): 51

Consumption (L/h): 5.4 at 75% of the load / 7.1 at 100% of the load





Running time (h): 9.4 at 75% of the load / 7.2 at 100% of the load

Length (mm): 2000

Width (mm): 920

Height (mm): 1100

Dry weight (Kg): 700

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Perkins

