



PRAMAC GSL42D COFANATO CON QUADRO COMANDO MANUALE

Product description:

Motore Diesel. Predisposto per Biodiesel. Raffreddamento ad olio con radiatore. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica

Product features:

Phase: Three phase

Maximum power three phase (KW): 35.62

Continuous power three phase (KW): 33.85

Maximum power three phase (KVA): 44.52

Continuous power three phase (KVA): 42.31

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 63A 3P+N+T - 1 x 400V 32A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Deutz AG BF4M2011, turbo

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 3110

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 10

Cooling: Oil

Alternator: Mecc Alte ECO/P32-3S/4, brushless

Poles: 4

Fuel tank capacity (L): 68





Consumption (L/h): 8.1 at 75% of the load / 11.2 at 100% of the load

Running time (h): 8.4 at 75% of the load / 6 at 100% of the load

Acoustic power: 89 dB(A)

Acoustic pressure: 60 dB(A) at 7 m

Length (mm): 2000

Width (mm): 920

Height (mm): 1310

Dry weight (Kg): 824

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Deutz