



PRAMAC GSL65D

Product description:

Motore Diesel. Predisposto per Biodiesel. Raffreddamento ad olio con radiatore. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica

Product features:

Phase: Three phase

Maximum power three phase (KW): 48.76

Continuous power three phase (KW): 46.23

Maximum power three phase (KVA): 60.95

Continuous power three phase (KVA): 57.79

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: Deutz AG BF4M2011C, turbo intercooled

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 3110

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 10

Cooling: Oil

Alternator: Mecc Alte ECO/P32-2L/4, brushless

Poles: 4

Fuel tank capacity (L): 91

Consumption (L/h): 9.9 at 75% of the load / 13.4 at 100% of the load

Running time (h): 9.2 at 75% of the load / 6.8 at 100% of the load

Length (mm): 2007

Width (mm): 758

Height (mm): 1841

Dry weight (Kg): 858

Silenced: No

Super silenced: No





Shop name

ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Deutz



PrestaShop