



# TRAILER ADAM15

## Product description:

ADAM15 Trailer

ADAM15 Trailer: Power and Versatility at Your Service

The ADAM15 trailer is a concentrate of strength and functionality, designed to meet the needs of the most demanding professionals.

Constructed with a heavy-gauge, hot-dip galvanised steel frame, this trailer guarantees a long service life and exceptional resistance to corrosion and weathering.

## Key Features:

**Unrivalled Robustness:** The welded steel frame, material thickness and hot-dip galvanising make the ADAM15 Trailer extremely strong and durable.

**Advanced Functionality:** The tilting platform with manual hydraulic pump and double piston, aluminium loading ramp and retractable lashing hooks make loading and unloading quick and safe.

**Safety and Stability:** The double axle with torsion bar suspension and independent wheels, together with the mechanical inertia braking system, guarantee excellent stability and safety while driving.

**Comfort and Functionality:** The under-floor wheels and V-shaped drawbar with automatic wheel make manoeuvring easy, while the perimeter railing and movable front bar provide safe loading.

**Modern Design:** The full LED system and designer lights give the trailer a modern, eye-catching appearance.

**Versatility:** With its generous internal dimensions and payload capacity, the ADAM15 trailer is ideal for transporting a wide range of materials, from machinery to bulky goods.

## Technical Data:





Steel trailer, welded, high thickness and quality, hot-dip galvanised,  
with V-shaped drawbar with automatic wheel.

Under-floor wheels.

Phenolic marine wood deck, bolted (not riveted) with noise-reducing coated hooks,  
for anchoring goods, concealed on the sides.

Railing on three sides h. 100 mm. with movable front bar to stop wheels.

Tilting floor with manual hydraulic pump and double piston.

Aluminium loading ramp, reinforced full-width, liftable, h. 600 mm.

Double axle (KNOTT or AL-KO) with torsion bar suspension, independent wheels and Inertia  
braking system.

Independent and Mechanical Inertia Braking System, with automatic reverse gear.

Wheels 155/70R12 C.

Full LED system (12 Volt.) with design lights and 13 PIN power socket.

Type approval "Transport of Goods" with European COC.

Useful floor dimensions, approx. = 5170 x 2095 x 100 mm.

Overall dimensions, approx. = 6670 x 2170 mm.

Weight when fully loaded = 3500 kg.

Tare Weight, approx. = 900Kg.

Looking for a trailer with different features? Here you can find the whole range of trailers

Pictures and technical data not binding.

**Product features:**

Trailer type : Goods transport





Struttura rimorchio: FLATBED/TRUNK

Tare mass (Kg): 900

Wheels: 155/70R12 C

Massa complessiva (Kg): 3500

Dimensione utile (mm): 5170 x 2095 x 100

Dimensione max (mm): 6670 x 2170

