



GENSET SILENCED 33 KVA

Product description:

GENSET SILENCED 33 KVA

SILENCED GENERATOR 33 KVA: Power and Reliability at your fingertips

The SILENCED GENERATING UNIT 33 KVA is a powerful electric generator designed to provide reliable and silent emergency or continuous power. With a maximum output of 33 kVA and a Baudouin 4M06G35/5 diesel engine, this generator set is the ideal solution for a wide range of applications, both domestic and industrial.

Key features:

Powerful and reliable: The Baudouin diesel engine ensures high performance and a long service life.

Quiet: Thanks to its soundproof housing, the noise level at 7 metres is only 70 dB(A), ensuring discrete operation.

Versatile: The 230V/400V output voltage and 50 Hz frequency make it compatible with most household appliances and equipment.

Autonomy: The 100-litre tank guarantees a long operating autonomy.

Compact dimensions: With its small size (2100x870x1165 mm), it can be easily transported and installed.

Low emissions: The engine complies with emission regulations, respecting the environment.

Technical characteristics SILENCED ELECTROGEN GROUP 33 KVA:

Type of phase: Three-phase

Three-phase continuous power: 24 kW

Three-phase continuous power: 30 kVA





Maximum three-phase LTP power: 26.4 kW
Maximum three-phase LTP power: 33 kVA
Fuel: Diesel
Voltage: 230V/400V
Frequency: 50 Hz
Manufacturer and type: Baudouin 4M06G35/5
1500 rpm
Displacement: 2300 cc.
Alternator MECC ALTE ECP28-VL4 4 poles
Noise level at 7 m: 70 dB(A)
Tank: 100 Lt.
Length: 2100 mm
Width: 870 mm
Height: 1165 mm
Dry weight: 940 Kg. approx.
Emission level: not emitted

If you are looking for a product with similar characteristics [CLICK HERE](#).

Non-binding images and technical data.

Product features:

Phase: Three phase
Maximum power three phase (KW): 26.4
Continuous power three phase (KW): 24
Maximum power three phase (KVA): 33
Continuous power three phase (KVA): 30
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: Baudouin 4M06G35/5
Emissions Regulations: Not Emitted
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Electric
Engine capacity (cm³): 2300
Number cylinders: 4
Alternator: MECC ALTE ECP28-VL/4
Poles: 4
Protection degree: IP23
Motor insulation class: H
Fuel tank capacity (L): 100





Consumption (L/h): 5.61 at 75% of the load

Acoustic pressure: 70 dB(A) at 7 m

Length (mm): 2100

Width (mm): 870

Height (mm): 1165

Dry weight (Kg): 940

Silenced: Yes

ATS Switch device : Optional

Engine manufacturer: Baudouin