



NED 88KW Stage II generator set

Product price:

27.992,33 € tax excluded

Product description:

NED Generator Set 88KW Stage II

The NED 88KW Stage II Generating Set is an industrial electric generator designed to offer exceptional performance and maximum reliability, even in the most demanding conditions. With a continuous output of 88 kW and an FPT NEF45TM2A engine, this generator set is the ideal solution for a wide range of applications, providing emergency or continuous power supply.

Key Features:

Powerful and reliable: The 4-cylinder FPT NEF45TM2A engine, with a displacement of 4.5 liters, ensures high performance and a long service life.

Quiet: Thanks to the soundproofed construction with class A1 rock wool, the noise level is extremely low, ensuring discrete operation.

Versatile: Available in single-phase and three-phase configurations, with an output voltage of 230/400 V and a frequency of 50 Hz, it adapts to various application requirements.

Economical: Low consumption of 15.75 l/h at 75% load makes it a cost-effective solution.

Robust: The galvanized steel construction and high-quality components guarantee a long service life.

Environmentally friendly: Compliant with Stage II emission regulations and environmentally friendly.

Technical characteristics:





Phase Type: Single Phase / Three Phase
Maximum Power: 110 KVA / 88 KW
Continuous Power: 100 KVA / 80 KW
Voltage: 230/400 V
Frequency: 50 Hz
Engine: FPT NEF45TM2A}
Standard emissions: Stage II
Number of cylinders: 4
Displacement: 4.5 l
Engine revs: 1500
Acoustic power: 55 db (A) at 7m
FUEL CONSUMPTION 75% (l/h): 15.75
Cooling: water
Regulator: AVR
Length: 3000 mm
Width: 1500 mm
Height: 2000 mm
Net weight: 2800 kg
Tank: 360 L
Structure material: Galvanized steel
Soundproofing material: Rock wool with resistance class a1
Alternator: Stamford
Insulation Class: H
Degree of protection: IP23
number of poles: 4

Are you looking for a product with different technical characteristics? HERE you can find the area dedicated to WHISPER vehicle generators or those of other specialized brands.

Images and non-binding technical data.

Product features:

Phase: Single phase / Three phase
Maximum power three phase (KW): 88
Continuous power three phase (KW): 80
Maximum power three phase (KVA): 110
Continuous power three phase (KVA): 100
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: FPT NEF45 TM2A
Emissions Regulations: Stage 2
Engine rpm (rpm): 1500





Engine capacity (cm³): 4500

Number cylinders: 4

Cooling: Water

Tank capacity (L): 360

Consumption (L/h): 75% (l/h) 15,75

Acoustic pressure: 55 dB(A) at 7 m

Length (mm): 3000

Width (mm):

Height (mm): 360

Dry weight (Kg): 2800

Silenced: Yes

Product type: Generator

Engine manufacturer: FPT Iveco

