



ITALTOWER MT55 TORRE FARO 4x160 W MULTILED (copia)

Product price:

1.952,00 € tax excluded

Product description:

LIGHTHOUSE TOWER 4x160 W MULTILED

Torre Faro is a manually hoisted light tower equipped with 4 floodlights capable of delivering a light output of 160W each.

Torre Faro is equipped with a galvanised steel lifting tower capable of extending up to a maximum height of 5.5 metres. The tower is complete with a hand pump for raising and manual locking on each section to prevent rotation of the sections and to guarantee maximum column extension even in the absence of air inside.

Torre Faro stands out for its performance, compactness and solidity, with its 4x160W LED lights, able to compete with much bulkier lighting towers equipped with a halogen system.

The light tower is suitable for a variety of large-scale construction work, maintenance repair, accident management and disaster relief work, and high-brightness lighting needs.

Light Tower is designed to be combined with a generator set and can be connected in series in order to use one generator for several lighting units.

The lightness of the Torre Faro will also allow you to move it easily and thanks to the 4 feet, which can be removed and folded to optimise the space inside the container, you will be able to light whatever you want.

TECHNICAL CHARACTERISTICS Lighthouse Tower:

Number of luminaires: 4

Lamp wattage: 160 W LED





Lumen: 81400 lm
Illuminated area: 2400 sqm
Voltage: 230 V
Frequency: 50 Hz
Consumption: 4 X 160W = 0.64 KW
Maximum height: 5.5m
Lifting system: Manual
Wind resistance: 80 Km/h
Trolley: Stationary
Stabilisers: 4
Length (mm): 640
Width (mm): 355
Height (mm): 1920
Dry weight (kg): 95

Looking for a light tower with different technical characteristics? [HERE](#) you can find the entire range of specialised light towers.

Images and technical data are not binding and may be subject to revision by the manufacturer.

Product features:

Frequency (Hz): 50
Voltage (V): 230
Maximum height (m): 5.5
Type of lamps: LED
Lamps: 4 x 160 W
Telescopic pole: Vertical
Illuminated area (m²): 2400
Total lumens (Lm): 81400
Lifting System: Manual lifting system
Open size (mm): 2200 x 2200 x 5700
Length closed (mm): 355
Width closed (mm): 640
Height closed (mm): 1920
With generator / Without generator: Without generator
Transportability: Stationary
Stability to wind (Km/h): 80 Km/h
Weight (Kg): 95

