



TECNOGEN AP40TL-IPA THREE-PHASE PTO GENERATOR 40KVA

Product price:

6.060,00 € tax excluded

Product description:

TECNOGEN AP40TL-IPA THREE-PHASE CARDAN GENERATOR 40KVA

TECNOGEN AP40TL-IPA THREE-PHASE PTO DRIVE GENERATOR 40KVA: Industrial power for versatile applications

The TECNOGEN AP40TL-IPA is a powerful 40 kVA three-phase cardan electric generator designed to provide reliable, continuous power in a wide range of applications. With its robust construction and state-of-the-art technologies, this generator is the ideal choice for construction sites, farms, outdoor events and industries that require an independent and flexible power source.

Key features:

High power: With a power rating of 40 kVA, this generator is capable of powering a wide variety of equipment and machinery, even under demanding load conditions.

Robustness and reliability: Constructed from high-quality materials and equipped with a robust frame, the TECNOGEN AP40TL-IPA is designed to withstand harsh operating conditions for a long time.

Versatility: The presence of several sockets, with different amperatures and configurations, allows a wide range of electrical devices to be connected.

Safety: The generator is equipped with numerous protection devices, such as thermal and differential relays, which guarantee maximum safety for operators and connected equipment.

Ease of use: The intuitive control panel and multifunctional digital instrument make it easy to monitor and control the generator.

Technical characteristics:

40 (32) kVA (kW) - cosPhi 0.8 400V 50HZ





Sockets:

1x32A 5p h6

1x16A 5p h6

1x16A 3p h6

1x63A 5p h1 spec.

Coupling category 2

Power take-off: 1",3/8 Z6

Transmission ratio: 1:3.5

No. of revolutions PTO -U/min. (50HZ): 430

Min. power PTO shaft - kW (HP): 45 (61)

Tractor Power (PS) ? : > 100

Length: 1000 mm

Width: 670 mm

Height: 1100 mm

weight: 350 kg

If you are looking for another product then you can see on our catalog other cardan shaft generators.

Images and technical data are not binding.

Product features:

Maximum power three phase (KW): 32

Maximum power three phase (KVA): 40

Sockets configuration: 1x32A 5p h6 1x16A 5p h6 1x16A 3p h6 1x63A 5p h1 spec.

Transmission ratio: 1 : 3.5

Length (mm): 1000

Width (mm): 670

Height (mm): 110

Weight (Kg): 350

Power take-off: 1",3/8 Z6

No. of revolutions PTO -U/min. (50HZ): 430

Min. power at PTO shaft - kW (HP): 45 (61)

Tractor Power (PS) ? : Greater than 100