



# WhisperPower MCC 24-12 VDC 5A B2B battery charger

**Product price:**

**96,00 € tax excluded**

**Product description:**

WhisperPower MCC 24-12 VDC 5A B2B charger

The WhisperPower MCC 24-12 VDC 5A B2B is a high-quality electronic device designed to efficiently and safely convert 24 Volts to 12 Volts. This converter is ideal for a wide range of applications, such as motorhomes, boats, commercial vehicles and off-grid power systems.

**Key features:**

**Efficient conversion:** Converts voltage from 24V to 12V with over 92% efficiency, minimising energy losses.

**Intelligent battery charging:** Uses a three-stage charging process, ensuring fast, efficient and safe charging of 12V batteries.

**Built-in protections:** Features protections against short circuits, overcharging and overheating, ensuring long life and safe operation.

**Voltage regulation:** Allows the output voltage to be adjusted between 12V and 15V, adapting to different needs.

**Temperature sensor:** The integrated temperature sensor allows the internal temperature to be monitored and the operation of the converter to be adjusted accordingly.

**Dimming function:** Can be used to adjust the intensity of 12V lighting.

**Compact and robust:** Its small size and robust construction make it easy to install and suitable for various applications.

**Regulatory Compliance:** Meets numerous international standards, ensuring product quality and





safety.

### Technical characteristics:

Weight (Kg) 0.270  
Nominal input voltage 24 VDC  
Input range, specifications met 24 ... 32 VDC  
Rated output voltage 13.8 VDC  
adjustable voltage 12/ 15 VDC  
Adjustable voltage 12 ... 15 VDC  
maximum output power 70 W  
Maximum output current (A) 5  
Continuous output current at 40 °C up to 5 A  
Efficiency >92%.  
Dimensions: 50x98x88 mm  
Weight: 0.27 kg  
Input voltage: 24-32 VDC  
Operating temperature: -10°C to +40°C

If you are looking for a product with similar characteristics CLICCA QUI.

Images and technical data are purely indicative.

### Product features:

Product dimensions (mm):  
Maximum output current (A): 5  
Weight (Kg): 0.270  
Nominal input voltage: 24 VDC  
Input range, specifications met: 24 .. 32 VDC  
nominal output voltage: 13.8 VDC  
adjustable tension: 12/ 15 vdc  
Adjustable tension: 12 .. 15 VDC  
maximum power output: 70 W

