



# PRAMAC GSW15Y ENCLOSURE WITH MANUAL CONTROL PANEL

**Product price:**

**11.347,50 € tax excluded**

## **Product description:**

PRAMAC GSW15Y Three-phase 11.6 KW generator set with diesel engine at 1500 rpm.

The PRAMAC GSW15Y generator set is equipped with electric start. The three-phase alternator of the PRAMAC GSW15Y generator set is brushless Mecc Alte with AVR voltage regulator. The Yanmar diesel engine makes the GSW15Y generator set very reliable as it has been built and designed using high quality materials.

Thanks to its enclosure, this generator set is super-silenced. In addition, it is easy to transport, install and position thanks to its compact size, making this model ideal for mains emergency, construction, mobile workshops and industrial applications. The three-phase PRAMAC GSW15Y generator set is suitable for outdoor use on construction sites or for small professional outdoor jobs.

## **Technical characteristics of the PRAMAC GSW15Y MCP Three-phase generator set:**

Maximum three-phase power: 11.6 KW

Continuous three-phase power: 10.59 KW

Fuel: Diesel

Voltage: 400 V

Frequency: 50 Hz

Engine: Yanmar 3TNV88-BGPGE

Starting: Electric

Consumption: 4 Lt/h at 100% load

Length: 1800 mm

Width: 850 mm





Height: 1260 mm

Weight: 580 Kg

AVR

**Sockets:**

\* N.1 3P+N+T CEE 400V 32A

\* N.1 3P+N+T CEE 400V 16A

\* N.2 2P+T CEE 230V 16A

\* N.1 230V 16A SCHUKO

The PRAMAC GSW15Y power generator is a professional diesel generator developed by Pramac that offers many solutions for a variety of applications, from continuous to emergency network use. The PRAMAC GSW15Y power generator complies with safety and noise emission regulations and can be used in both residential and industrial settings. The GSW15Y generator is equipped with a reliable Yanmar diesel engine, and various control panel solutions, supplements, and accessories make it versatile and capable of meeting the most demanding customer needs.

If you are looking for a generator like the GSW15Y MCP three-phase power generator, then we recommend browsing our catalog of land-based generators to find the one that best suits your needs.

Images and technical data are not binding.

**Product features:**

Phase: Three phase

Maximum power three phase (KW): 11.6

Continuous power three phase (KW): 10.59

Maximum power three phase (KVA): 14.5

Continuous power three phase (KVA): 13.24

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Yanmar 3TNV88-BGPGE, naturally aspirated

Emissions Regulations: Stage 5





Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 1642

Number cylinders: 3

Cylinders' position: In line

Oil capacity (L): 6.9

Cooling: Water

Alternator: Mecc Alte ECP3-2L, brushless

Poles: 4

Fuel tank capacity (L): 68

Consumption (L/h): 3 at 75% of the load / 4 at 100% of the load

Running time (h): 22.8 at 75% of the load / 17.2 at 100% of the load

Acoustic power: 94 dB(A)

Acoustic pressure: 65 dB(A) at 7 m

Length (mm): 1800

Width (mm): 850

Height (mm): 1260

Dry weight (Kg): 580

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Yanmar

