



# WEBASTO BLUECOOL VX36M Chiller con regolazione della velocità variabile 3400 BTU/h

**Product price:**

**7.299,00 € tax excluded**

**Product description:**

WEBASTO BLUECOOL VX36M Variable Speed Chiller 3400BTU/h

WEBASTO BLUECOOL VX36M Variable Speed Chiller 3400BTU/h represents a cutting-edge solution for air conditioning,

offering high performance and optimal energy efficiency. With a variable cooling capacity from 3,400 to 36,000 BTU/h (1 to 10.5 kW),

this chiller is able to adapt to different air conditioning needs, ensuring constant comfort in every situation.

Performance and Versatility WEBASTO BLUECOOL VX36M Chiller :

**Heating Capacity:** In reverse cycle mode, the WEBASTO BLUECOOL VX36M offers a heating capacity of 44,400 BTU/h (12.9 kW), making it ideal for use in different seasons.

**Compact Dimensions:** The dimensions of 533 x 352 x 378 mm (21 x 13.9 x 14.9 inches) make it easy to install even in tight spaces.

**Power Supply:** Designed to operate with a voltage of 230V 1-Phase and a frequency of 50/60 Hz, it is compatible with most electrical systems.





Efficiency and Sustainability WEBASTO BLUECOOL VX36M Chiller :

Variable Current Absorption: The current absorption varies from 3 to 13.5 A in normal operation, with an ECO mode that further reduces consumption (10 – 7 – 4.3 A).

High Energy Efficiency: With an EER up to 4.3, the WEBASTO BLUECOOL VX36M ensures high energy efficiency, reducing operating costs.

Ecological Refrigerant: The use of R32 refrigerant with a GWP of 675 helps reduce environmental impact.

**Technical Features WEBASTO BLUECOOL VX36M Chiller :**

Cooling Capacity [BTU/h] [kW]: 3,400 – 36,000 (1 – 10.5)

Heating Capacity [BTU/h] [kW] (Reverse Cycle Mode): 44,400 (12.9)

Dimensions (H/W/D) [mm] [Inches]: 533 x 352 x 378 (21 x 13.9 x 14.9)

Voltage/Phase: 230V 1-Phase

Frequency [Hz]: 50 / 60

Current Absorption in Operation [A]: 3-13.5 (max. 15)

Current Absorption ECO Mode (1 – 2 – 3) [A]: 10 – 7 – 4.3

Start Current Absorption [A]: 3

Chilled Water Connection [mm][inches]: IG25 BSPP Female 1

Sea Water Connection [l/min]: IG25 BSPP Female 1

Minimum Flow Rate Sea Water / Chilled Water [l/min]: 40 / 33

Weight [kg]: 49

Energy Efficiency (EER): Up to 4.3

Refrigerant / GWP: R32 / 675

Looking for a product with different technical features? [HERE](#) you can find the area dedicated to WEBASTO marine air conditioners or those from other specialized brands.





Images and technical data are non-binding.

**Product features:**

Phase: Single phase

Frequency (Hz): 50 / 60

Voltage (V): 230

Product dimensions (mm): 533 x 352 x 378

Refrigerating yield: 3.400 BTU/h / kW 36.000

Heating power: 44.000 btu/h / KW 12.9

Coolant: R32

Weight (Kg): 49

Current consumption: 3-13.5 A (max. 15)

Assorbimento di Corrente Modalità ECO (1 – 2 – 3) [A]: 10 - 7 - 4.3

Minimum seawater/chilled water flow rate [l/min].: 40 / 33

Current consumption Start A: 3

Sea Water Connection [l/min]: IG25 BSPP Female 1

Chilled Water Connection [mm][inch]: IG25 BSPP Female 1

