



Generator Set 33KVA SuperSilent STAGE V

Product price:

14.267,00 € tax excluded

Product description:

33KVA Silenced Generator Set STAGEV

The **33KVA Silenced Generator Set STAGEV** is the ideal solution for those seeking a powerful and quiet generator, compliant with the latest environmental standards. With a maximum three-phase power of 30 kW (33 kVA), this generator set can power a wide range of applications, ensuring stable and reliable power delivery.

The YANMAR 4TNV98 engine, compliant with Stage 5 emission standards, ensures efficient and low environmental impact operation; with a speed of 1500 rpm, the engine guarantees optimal stability of power delivery.

The LINZ PRO18 SC/4 (*) alternator provides a stable voltage of 230/400V at 50Hz, ensuring compatibility with various equipment.

The silenced configuration minimizes noise, making it suitable even for sensitive environments; the 120-liter fuel tank ensures excellent autonomy, allowing for prolonged uninterrupted operation.

With dimensions of 2260x1000x1165 mm and a dry weight of 1100 Kg, this generator set is designed to be robust and easy to install.

The electric start allows for simple and quick start-up; the optional ATS switching panel automatically manages emergency power.

In summary, the **33KVA Silenced Generator Set STAGEV** is the perfect choice for those who need a reliable, quiet, and environmentally friendly generator.

Its compliance with Stage 5 standards, combined with its high performance and quiet operation, makes it suitable for a wide range of applications, from construction sites to emergency situations, and wherever reliable and low-noise electrical power is required.

TECHNICAL SPECIFICATIONS 33KVA Silenced Generator Set STAGEV:





Phase type: Single phase/Three phase
Maximum three-phase power: 30 kW
Maximum three-phase power: 33 kVA
Frequency: 50 Hz
Voltage: 230 / 400 V
Engine: YANMAR 4TNV98
Engine speed: 1500 rpm
Start: Electric
Alternator: LINZ PRO18 SC/4 (*)
Fuel tank capacity: 120 liters
Length: 2260 mm
Width: 1000 mm
Height: 1165 mm
Dry weight: 1100 Kg
Silenced: Yes
ATS switching panel: Optional
Emission standard: Stage 5

Looking for a generator set with different technical characteristics? [HERE](#) you will find a selected range of products.

Images and technical data are not binding. Always consult the technical data sheet issued by the manufacturer.

Manel Service does not assume responsibility for any changes made by the manufacturer.

Product features:

Phase: Single phase / Three phase
Maximum power three phase (KW): 30
Maximum power three phase (KVA): 33
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: YANMAR 4TNV98C
Emissions Regulations: Stage 5
Engine rpm (rpm): 1500
Starting system: Elettrico
Alternator: LINZ PRO18 SC/4 (*)
Fuel tank capacity (L): 120
Length (mm): 2260
Width (mm): 1000
Height (mm): 1165





Dry weight (Kg): 1100

Silenced: Yes

ATS Switch device : Optional