



PRAMAC GSW10Y COFANATO CON QUADRO COMANDO MANUALE (MCP)

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 176

Continuous power three phase (KW): 162.22

Maximum power three phase (KVA): 220

Continuous power three phase (KVA): 202.78

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: FPT NEF67TE2A, turbo aftercooler

Speed governor: Electronic

Starting system: Electric

Engine capacity (cm³): 6

Number cylinders: 6

Cylinders' position: In line

Oil capacity (L): 17

Cooling: Water

Alternator: Mecc Alte ECO38-2SN/4, brushless

Poles: 4

Fuel tank capacity (L): 350

Consumption (L/h): 33.5 at 75% of the load / 44 at 100% of the load

Running time (h): 10.4 at 75% of the load / 7.9 at 100% of the load

Acoustic power: 97 dB(A)

Acoustic pressure: 68 dB(A) at 7 m

Length (mm): 3400





Shop name

Width (mm): 1250

Height (mm): 1770

Dry weight (Kg): 2145

Inverter: No

AVR: Yes

Compound: No

Silenced: Yes

Super silenced: Yes



PrestaShop