



PRAMAC GSW67P COFANATO CON QUADRO COMANDO MANUALE

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 53.28

Continuous power three phase (KW): 48.76

Maximum power three phase (KVA): 66.6

Continuous power three phase (KVA): 60.95

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: PERKINS 1104D-44TG3, turbocharged

Emissions Regulations: Stage 3A

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 4400

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 8

Cooling: Water

Alternator: Mecc Alte ECO/P32-2L/4, brushless

Poles: 4

Fuel tank capacity (L): 209

Consumption (L/h): 12 at 75% of the load / 16 at 100% of the load

Running time (h): 17.4 at 75% of the load / 13 at 100% of the load

Acoustic power: 96 dB(A)

Acoustic pressure: 67 dB(A) at 7 m





Length (mm): 2285

Width (mm): 920

Height (mm): 1465

Dry weight (Kg): 1150

Silenced: Yes

Super silenced: Yes

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Perkins