



---

# WFM SE12000-MTHE AVR

## Product description:

## Product features:

Phase: Single phase / Three phase  
Maximum power single phase (KW): 8.8  
Continuous power single phase (KW): 7.9  
Maximum power single phase (KVA): 11  
Continuous power single phase (KVA): 9.9  
Maximum power three phase (KW): 26.4  
Continuous power three phase (KW): 24  
Maximum power three phase (KVA): 33  
Continuous power three phase (KVA): 30  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine: John Deere 3029 DF 128, naturally aspirated  
Engine rpm (rpm): 1500  
Speed governor: Mechanical  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 2900  
Number cylinders: 3  
Cooling: Water  
Alternator: Mecc Alte ECO 28 VL4, brushless  
Poles: 4  
Bore x stroke (mm): 106 x 110  
Fuel tank capacity (L): 135  
Consumption (L/h): 7 at 100% of the load  
Running time (h): 19.28 at 100% of the load  
Acoustic pressure: 67 dB(A) at 7 m  
Length (mm): 1940  
Width (mm): 1000





---

Height (mm): 1480  
Dry weight (Kg): 960  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: John Deere