



WFM SE12000-MTHE AVR

Product description:

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 11.7
Continuous power single phase (KW): 10.6
Maximum power single phase (KVA): 14.6
Continuous power single phase (KVA): 13.4
Maximum power three phase (KW): 35.2
Continuous power three phase (KW): 32
Maximum power three phase (KVA): 44
Continuous power three phase (KVA): 40
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: John Deere 3029 TF 158, turbocharged
Engine rpm (rpm): 1500
Speed governor: Mechanical
Starting system: Electric
Engine capacity (cm³): 2900
Number cylinders: 3
Cooling: Water
Alternator: Mecc Alte ECO 32 3S, brushless
Poles: 4
Bore x stroke (mm): 106 x 110
Fuel tank capacity (L): 135
Consumption (L/h): 8 at 100% of the load
Running time (h): 16.87 at 100% of the load
Acoustic pressure: 67 dB(A) at 7 m
Length (mm): 1940
Width (mm): 1000



Height (mm): 1480
Dry weight (Kg): 1020
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: John Deere