



# GENSET MG 8000 BS/HA SINGLE-PHASE POWER GENERATOR 7 KVA AVR

**Product price:**

**3.156,00 € tax excluded**

## **Product description:**

GENSET MG 8000 BS/HA SINGLE-PHASE POWER GENERATOR 7 KVA AVR

GENSET MG 8000 BS/HA Single-phase generating set with Honda GX 390 OHV STAGE V engine powered by gasoline, capable of delivering a maximum power of 7 KVA complete with AVR voltage regulator.

The GENSET MG 8000 BS/HA generator set is compact and easy to use, equipped with a casing that lowers noise emissions and makes it super-silenced.

The GENSET MG 8000 BS/HA is equipped with electric start with 12 V battery and low fuel consumption, in fact it consumes only 3.3 liters/hour at 75% load.

The generator set GENSET MG 8000 BS/HA is part of the silenced series and are characterized by lower consumption and a longer life expectancy than the range powered by gasoline and equipped with soundproof cabin suitable for installation and outdoor use, and increased tank. The GENSET MG 8000 BS/HA generator set at 3000 rpm is suitable for emergency use only. It is not recommended to use it for more than 6 continuous hours and for more than 500 hours per year.

## TECHNICAL FEATURES GENSET MG 8000 BS/HA

Phase Type: Single-Phase

Maximum Single-Phase Power: 7 KVA / 5.6 KW

VAC Voltage: 230 / 400 V

Frequency (Hz): 50

Quadro Starter: Manual with self-winding

Motor: Honda GX 390 OHV

Emission Standard: STAGEV

RPM: 3000

Power supply: Gasoline





Fuel tank capacity: 10.5 l  
Consumption @ 75 % load: 3.3 l/h  
Autonomy @ 75 % load: 3.18 h  
Sound pressure: 86 dB(A)  
Length: 1059 mm  
Width: 670 mm  
Height: 740 mm  
Net weight: 138 Kg

Are you looking for a generator with different technical characteristics? Here you can find the full range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revisions by the manufacturer.

**Product features:**

Phase: Single phase  
Maximum power single phase (KW): 5.6  
Maximum power single phase (KVA): 7  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 1 x 230V 16A CEE - 1 x 230V 32A CEE  
Engine: Honda GX390, 4 stroke, OHV  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 390  
Number cylinders: 1  
Cooling: Air  
Alternator: Synchronous  
Protection degree: IP23  
Motor insulation class: H  
Fuel tank capacity (L): 10.5  
Consumption (L/h): 3.3  
Running time (h): 3.18  
Acoustic power: 86 dB(A)  
Acoustic pressure: 61 dB(A) at 7 m  
Length (mm): 1059  
Width (mm): 670  
Height (mm): 740  
Dry weight (Kg): 138  
Silenced: Yes



---

Super silenced: Yes  
Product type: Generator  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Honda