



# GENSET MG 10001 SS-KL - GENERATOR 10 KVA

**Product price:**

**6.726,00 € tax excluded**

## **Product description:**

GENSET MG 10001 SS-KL SINGLE PHASE GENERATOR 10KVA

GENSET MG 10001 SS-KL Single-phase generating set with Kubota D1105 StageV engine powered by diesel, capable of delivering a maximum power of 10KVA.

The GENSET MG 10001 SS-KL generator set is compact and easy to use, equipped with enclosure that lowers noise emissions and makes it super-silenced.

The GENSET MG 10001 SS-KL is a single-phase 10KVA diesel generator set with electric start. This generator is also available in a version with an automatic panel and remote control.

Thanks to its compact size and very low weight, the GENSET MG 10001 SS-KL is a lightweight generator that is easy to transport. The GENSET MG 10001 SS-KL also has a low fuel consumption: only 2 Lt/h at 75% load.

The GENSET MG 10001 SS-KL generator set, thanks to the high quality and efficiency of its components, is ideal for various types of work: from small hobby work to large construction sites.

The GENSET MG 10001 SS-KL generator set includes:

- Battery 12 V
- 1 single-phase socket CEE 230V - 32A
- 1 single-phase socket CEE 230V - 16A
- 1 single-phase socket SCHUKO 230V - 16A
- Thermal protection
- Differential switch
- Emergency stop button
- Fuel level indicator
- Hour meter
- Bulb presence voltage 230V
- Central lifting hook





- Arrangement for operation in AMF-ATS or Remote Control
- Automatic engine stop device with warning lights for:
  - battery charge failure
  - high water temperature
  - low oil pressure

#### TECHNICAL FEATURES GENSET MG 10001 SS-KL

Phase Type: SinglePhase  
Maximum SinglePhase Power: 10 KVA / 8 KW  
Continuous SinglePhase Power: 9 KVA / 7.2 KW  
VAC Voltage: 230 V  
Frequency (Hz): 50  
Starting Frame: Electric  
Motor: Kubota D1105  
Emission Standard: Stage V  
RPM: 1500  
Power supply: Diesel  
Fuel tank capacity: 30 l  
Consumption @ 75 % load: 2 l/h  
Autonomy @ 75 % load: 15 h  
Sound pressure: 90 dB(A)  
Length: 1360 mm  
Width: 675 mm  
Height: 860 mm  
Net weight: 330 kg

Are you looking for a generator with different technical characteristics? Here you can find the whole range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revision by the manufacturer.

#### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 8  
Continuous power single phase (KW): 7.2  
Maximum power single phase (KVA): 10  
Continuous power single phase (KVA): 9  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 1 x 230V 16A CEE - 1 x 230V 32A CEE - 1 x 230V 16A SCHUKO





Engine: Kubota D1105  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 1500  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 1123  
Number cylinders: 3  
Cooling: Water  
Alternator: Synchronous  
Protection degree: IP23  
Motor insulation class: H  
Fuel tank capacity (L): 30  
Consumption (L/h): 2  
Running time (h): 15  
Acoustic power: 90 dB(A)  
Acoustic pressure: 65 dB(A) at 7 m  
Length (mm): 1360  
Width (mm): 674  
Height (mm): 860  
Dry weight (Kg): 330  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : Optional  
Voltage regulator: No  
Engine manufacturer: Kubota

