



GENSET MG 10/6 S-R - SINGLE-PHASE/THREE-PHASE GENERATOR 10 KVA

Product price:

5.184,62 € tax excluded

Product description:

GENSET MG 10/6 S-R SINGLE-PHASE / THREE-PHASE GENERATOR 10KVA

GENSET MG 10/6 S-R Singlephase / threephase generating set with Lombardini 25LD330/2 diesel engine, capable of delivering a maximum power of 10KVA with AVR **Optional** voltage regulator.

The GENSET MG 10/6 S-R generator set is compact and easy to use, equipped with enclosure that lowers noise emissions and makes it super-silenced.

The GENSET MG 10/6 S-R is a 10 KVA singlephase/threephase diesel generator set with electric start. This generator is also available in the version with AVR voltage regulator, with automatic panel and remote control.

Thanks to its compact size and very low weight, the GENSET MG 10/6 S-R is a lightweight generator that is easy to transport.

The GENSET MG 10/6 S-R also has a low fuel consumption: only 2.2 Lt/h at 75% load.

The GENSET MG 10/6 S-R generator set, thanks to the high quality and efficiency of its components, is ideal for various types of work: from small hobby work to large construction sites.

The generating GENSET MG 10/6 S-R includes:

- Voltmeter
- Hour meter
- Differential magnetothermal switch
- Emergency stop button
- Starting battery





- 1 threephase socket CEE 16A, 400V - 50 Hz
- 1 singlephase socket CEE 32A, 230V - 50 Hz
- 1 singlephase socket CEE 16A, 230V - 50 Hz
- Protection for power outputs
- Arrangement for operation in AMF/ATS or remote control
- Voltmetric switch
- Central lifting hook

TECHNICAL FEATURES GENSET MG 10/6 S-R

Phase Type: SinglePhase / ThreePhase
Maximum SinglePhase Power: 8.3 KVA / 6.64 KW
Maximum ThreePhase Power: 10 KVA / 8 KW
VAC Voltage: 230 / 400 V
Frequency (Hz): 50
Starting Frame: Electric
Engine: Lombardini 25LD330/2
Emission Regulations: Non-emitting
RPM: 3000
Power supply: Diesel
Fuel tank capacity: 10.5 l
Consumption @ 75 % load: 2.2 l/h
Autonomy @ 75 % load: 4.77 h
Sound pressure: 97 dB(A)
Length: 1000 mm
Width: 560 mm
Height: 730 mm
Net weight: 190 Kg

Are you looking for a generator with different technical characteristics? Here you can find the whole range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revision by the manufacturer.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 6.64
Maximum power single phase (KVA): 8.3
Maximum power three phase (KW): 8
Maximum power three phase (KVA): 10
Fuel: Diesel
Frequency (Hz): 50





Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A CEE - 1 x 230V 16A CEE - 1 x 230V 32A CEE

Engine: Lombardini 25LD330.2, 4 stroke

Emissions Regulations: Stationary Use

Engine rpm (rpm): 3000

Starting system: Electric

Engine capacity (cm³): 654

Number cylinders: 2

Cooling: Air

Alternator: Synchronous

Protection degree: IP23

Motor insulation class: H

Fuel tank capacity (L): 10.5

Consumption (L/h): 2.2

Running time (h): 4.77

Acoustic power: 97 dB(A)

Acoustic pressure: 72 dB(A) at 7 m

Length (mm): 1000

Width (mm): 560

Height (mm): 715

Dry weight (Kg): 190

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR (optional)

Engine manufacturer: Lombardini

