



HONDA EG 3600 CL D-Avr Single-Phase Petrol Generator 3.6 kW 4.5 kVA

Product price:

896,00 € tax excluded

Product description:

HONDA EG3600CL GENERATOR SINGLE-PHASE AVR 3,6KW 4,5KVA

HONDA EG3600CL is a singlephase **4,5KVA 3,6KW power generator** with gasoline operation and D-AVR technology.

The Honda EG3600CL generator is ideal for sensitive electronic equipment as well as the most demanding commercial and rental applications, they are always ready for work, anywhere, anytime.

It is good to know that you can always count on the voltage produced by the Honda EG3600cl generator, produced through an automatic digital voltage regulator (D-AVR). This regulator represents an improvement over the traditional AVR and provides smoother and more efficient power for sensitive electronic equipment, offering a stable 4,5KVA clean energy waveform.

The Honda EG3600cl becomes a reliable companion, ready to work every day of the week. Once in operation, it satisfies any request, also responding well to load variations.

The practical cap allows easy refueling without spilling fuel, it also allows you to control the fuel level without removing it, also offering significant time savings.

Highly practical sockets and controls allow quick and easy starting and operation, especially because the motor and starter, fuel tank cap, switch and plugs are all on the same panel. This allows easy and practical starting and operation of the Honda EG3600cl.

The **Oil Alert™ technology** will automatically disconnect the contact in case the oil is below the safety level.

Honda EG3600cl has a unique engine support system with a durable steel frame. These rubber dampers, positioned on both sides of the engine and inclined at 45°, significantly reduce the engine vibration of an already quiet machine. Beautiful from an aesthetic point of view, effective





from a functional point of view.

TECHNICAL FEATURES OF THE GENERATOR HONDA EG3600CL A SINGLE-PHASE AVR 3,6 kW 4,5kVA

Phase type: Single-phase
Maximum power: 3.6KW
Continuous use power: 3.2KW
Maximum power: 4.5KVA
Continuous use power: 4KVA
Fuel: Petrol
Voltage (V): 230
Frequency (Hz): 50 Hz
Engine: Honda GX270T2
Type: 4-stroke, OHV, 1 cylinder
Starter: recoil starter
Autonomy: 12h
Consumption: 2 Lt/h
Length: 681 mm
Width: 530 mm
Height: 571 mm
Weight (Kg): 68
D-Avr
Tank capacity: 24
Oil tank capacity: 1.1 L
Displacement (cm³): 270
Engine Revs: 3000
Ignition: Transistorised

Are you looking for a product with different characteristics? [HERE](#) you can find the whole range **HONDA** and other specialized brands.

Images and technical data of Honda EG3600cl 4,5KVA 3,6KW are not binding and subject to change by the manufacturer

Product features:

Phase: Single phase
Maximum power single phase (KW): 3.6
Continuous power single phase (KW): 3.2
Maximum power single phase (KVA): 4.5





Continuous power single phase (KVA): 4
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V 16A CEE - 1 x 230V 16A SCHUKO
Engine: Honda GX270 T2, 4 stroke, OHV
Engine rpm (rpm): 3000
Ignition: Transistorized
Starting system: Manuale
Number cylinders: 1
Oil capacity (L): 1.1
Cooling: Forced air
Alternator: Bipolar
Bore x stroke (mm): 77 x 58
Fuel tank capacity (L): 24
Consumption (L/h): 2
Running time (h): 12
Acoustic power: 96 dB(A)
Acoustic pressure: 79 dB(A)
Length (mm): 681
Width (mm): 530
Height (mm): 571
Dry weight (Kg): 68
Silenced: No
Super silenced: No
Product type: Generator
ATS Switch device : No
Voltage regulator: iAVR
Engine manufacturer: Honda

