



MASE MPV 22 BA

Product description:

OUT OF PRODUCTION

Single-phase maximum power: 13.5 KW
Three-phase maximum power: 17.6 KW
Three-phase continuous use power: 16 KW
Fuel: Diesel
Voltage: 230 V / 400 V
Frequency: 50 Hz
Engine: Yanmar 3TNV88
Starting: Electric
Consumption: 2.5 Lt / h at 75% of the load
Length: 1750 mm
Width: 800 mm
Height: 900 mm
Weight: 600 Kg
Compound

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 13.5
Maximum power single phase (KVA): 13.5
Maximum power three phase (KW): 17.6
Continuous power three phase (KW): 16
Maximum power three phase (KVA): 22
Continuous power three phase (KVA): 20
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 2 x 230V 16A CE
Engine: Yanmar 3TNV88, 4 stroke
Engine rpm (rpm): 1500





Speed governor: Mechanical
Starting system: Electric
Engine capacity (cm³): 2190
Number cylinders: 4
Oil capacity (L): 7.4
Cooling: Water
Inyección : Direct
Alternator: Synchronous self-excited, with brushes
Poles: 4
Lubrication: Forced
Fuel tank capacity (L): 50
Consumption (L/h): 2.5 at 75% of the load
Running time (h): 20 at 75% of the load
Acoustic power: 94 dB(A)
Length (mm): 1750
Height (mm): 900
Dry weight (Kg): 600
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: Compound
Engine manufacturer: Yanmar

