



---

# MASE MPV 44 BA

## Product description:

OUT OF PRODUCTION

Three-phase maximum power: 35.2 KW  
Three-phase continuous use power: 32 KW  
Fuel: Diesel  
Voltage: 230 V / 400 V  
Frequency: 50 Hz  
Engine: Deutz BF4M2011  
Starting: Electric  
Consumption: 5.61 Lt / h at 75% of the load  
Length: 1980 mm  
Width: 860 mm  
Height: 1090 mm  
Weight: 915 Kg  
AVR

## Product features:

Phase: Three phase  
Maximum power three phase (KW): 35.2  
Continuous power three phase (KW): 32  
Maximum power three phase (KVA): 44  
Continuous power three phase (KVA): 40  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 2 x 230V 16A CE  
Engine: Deutz BF4M2011, 4 stroke  
Engine rpm (rpm): 1500  
Speed governor: Mechanical  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 3108





Number cylinders: 4  
Oil capacity (L): 10  
Cooling: Oil  
Inyección : Direct  
Alternator: Synchronous self-excited, brushless  
Poles: 4  
Lubrication: Forced  
Fuel tank capacity (L): 50  
Consumption (L/h): 5.61 at 75% of the load  
Running time (h): 8.9 at 75% of the load  
Acoustic power: 95 dB(A)  
Acoustic pressure: 70 dB(A) at 7 m  
Length (mm): 1980  
Width (mm): 860  
Height (mm): 1090  
Dry weight (Kg): 915  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Deutz

