



TECNOGEN H15000TELX

Product price:

3.546,00 € tax excluded

Product description:

Generating sets available in both single-phase and three-phase versions, with powers from 4.5 to 13.3 kVA MAX, equipped with gasoline or diesel engines, air-cooled, 3000 rpm, with electric and / or manual start with self-winding. Characterized by a particularly sophisticated design, they also stand out in terms of the set-up. In fact, they have a complete coverage of the upper part consisting of a sturdy sheet metal roof with central lifting point, a 20 Lt tank in polyethylene and an electrical panel positioned in a special protected compartment, separated from the motor / alternator unit and therefore exempt. from vibrations, equipped with hour meter and magnetothermic / differential switch. Thanks to their features and the latest generation Honda engines, which allow the petrol versions to fall within the parameters of the noise directive 2000/14 / EC, the LX series generator sets are the ideal solution for operators who need generators equipped with a professional set-up while remaining in the range of non-soundproofed machines.

The image is purely indicative.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 3
Maximum power single phase (KVA): 3.8
Maximum power three phase (KW): 10.4
Maximum power three phase (KVA): 13
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: HONDA GC160
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 688
Number cylinders: 2



Cooling: Air

Fuel tank capacity (L): 20

Consumption (L/h): 7

Running time (h): 2.8

Acoustic power: 98 dB(A)

Length (mm): 990

Width (mm): 550

Height (mm): 670

Dry weight (Kg): 133

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: No

Engine manufacturer: Honda