



PRAMAC TG20/3 IP44 with RTE Single-phase-Three- phase Cardan Generator 18kVA

Product price:

1.989,00 € tax excluded

Product description:

PRAMAC TG20/3 IP44 with RTE PTO Generator Single/Three-Phase 18 KVA

PRAMAC TG20/3 IP44 with RTE PTO generator, 9 KVA single-phase and 18 KVA three-phase, with tractor connection at 3000 rpm. The PRAMAC TG20/3 IP44 PTO generator has a voltage of 230 V / 400 V and a frequency of 50 Hz. The alternator of the PRAMAC TG20/3 IP44 PTO generator has a **compound** voltage regulator. The compound regulator stabilizes the voltage and prevents damage to connected devices. The TG20/3 IP44 PTO generator is highly reliable as it has been built and designed using high-quality materials.

Easy to transport, install, and position thanks to its compact size, this model is ideal for mounting on a tractor unit. The PRAMAC TG20/3 IP44 PTO generator requires a tractor power of 37 kW / 50 HP and a PTO speed of 435 rpm.

Technical specifications of the PRAMAC TG20/3 IP44 PTO Generator Single/Three-Phase:

Continuous power single-phase: 9 kVA

Continuous power three-phase: 18 kVA

Voltage: 230 V / 400 V

Frequency: 50 Hz

PTO speed: 435 rpm

Required tractor power: 37 kW / 50 HP

Length: 958 mm

Width: 645 mm

Height: 1003 mm

Weight: 160 kg

Compound

Outlets:

N.1 SCHUKO 230V 16A IP54





N.1 2P+T CEE 230V 32A IP44

N.1 3P+N+T CEE 400V 32A IP44

The PRAMAC TG20/3 IP44 PTO generator is a professional tractor-driven unit developed by Pramac, making it one of the best choices compared to its competitors. The PRAMAC TG20/3 IP44 PTO generator features a robust structure with a protective tubular frame. This series is the ideal solution for agricultural applications and also allows access to hard-to-reach areas even under adverse weather conditions.

The TG20/3 IP44 PTO generator is equipped with thermal-magnetic protection, residual current protection, voltmeter, frequency meter, and out-of-limit voltage protection (min–max).

If you are looking for a PTO generator like the PRAMAC TG20/3 IP44 single/three-phase tractor-driven unit, we recommend browsing our catalog of PTO generators to find the one that best suits your needs.

Product features:

Phase: Single phase / Three phase

Continuous power single phase (KW): 6.4

Continuous power single phase (KVA): 9

Continuous power three phase (KW): 14.4

Continuous power three phase (KVA): 18

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine rpm (rpm): 3000

PTO speed (round/min): 435

Required tractor power: 37 KW / 50 HP

