



# PRAMAC TG42/15 IP23 Cardan generator Single- phase-Three-phase 42kVA AVR

**Product price:**

**3.732,00 € tax excluded**

**Product description:**

PRAMAC TG42/15 IP23 Cardan Generator Single/Three-Phase 42 kVA AVR

PRAMAC TG42/15 IP23 cardan generator, 14.7 kVA single-phase and 42 kVA three-phase, with tractor connection at 1500 rpm. The PRAMAC TG42/15 IP23 cardan generator has a voltage of 230 V / 400 V and a frequency of 50 Hz. The alternator of the PRAMAC TG42/15 IP23 cardan generator features an AVR voltage regulator. The TG42/15 IP23 AVR cardan generator is highly reliable, as it has been built and designed using high-quality materials.

Easy to transport, install, and position thanks to its compact size, this model is ideal for mounting on a tractor unit. The PRAMAC TG42/15 IP23 cardan generator requires a tractor power of 74 kW / 100 HP and a cardan shaft speed of 395 rpm.

**Technical specifications of the PRAMAC TG42/15 IP23 AVR Cardan Generator Single/Three-Phase:**

Continuous power single-phase: 14.7 kW

Continuous power three-phase: 33.6 kW

Voltage: 230 V / 400 V

Frequency: 50 Hz

Cardan shaft speed: 395 rpm

Required tractor power: 74 kW / 100 HP

Length: 1110 mm

Width: 720 mm

Height: 1322 mm

Weight: 355 kg

AVR

**Sockets:**

N.1 SCHUKO 230V 16A IP54





N.1 2P+T CEE 230V 32A IP44

N.1 3P+N+T CEE 400V 63A

The PRAMAC TG42/15 IP23 cardan generator is a professional tractor-driven unit developed by Pramac, making it one of the best choices compared to its competitors. The PRAMAC TG42/15 IP23 cardan generator features a robust structure with a protective tubular frame.

The TG42/15 IP23 cardan generator is equipped with thermal-magnetic protection, residual current protection, voltmeter, and frequency meter.

If you are looking for a cardan generator like the PRAMAC TG42/15 IP23 AVR single/three-phase tractor-driven unit, we recommend browsing our catalog of cardan generators to find the one that best suits your needs.

**Product features:**

Phase: Single phase / Three phase

Continuous power single phase (KW): 11.7

Continuous power single phase (KVA): 14.7

Continuous power three phase (KW): 33.6

Continuous power three phase (KVA): 42

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 63A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine rpm (rpm): 1500

PTO speed (round/min): 395

Required tractor power: 74 KW / 100 HP

Weight (Kg): 355

