



TECNOGEN PK71TSS

Product description:

The TENAX series includes diesel generators, 1500 rpm, water or air cooled, with power from 5.5 to 2255 kVA max, providing three-phase voltage 400/230 V.

Available in both open base and super silenced versions, they are equipped with Perkins, John Deere, Iveco Aifo or Lombardini industrial engines and alternators from leading global brands, such as Leroy Somer, Stamford, Mecc Alte or Marelli.

The canopies, designed to guarantee an excellent level of soundproofing and optimal engine cooling, are made entirely of hot-dip galvanized steel and subsequently painted with polyester powders, making them practically resistant to atmospheric agents. Due to their characteristics, these machines are particularly suitable for continuous use in industrial environments and, in the super-silenced versions, for applications with automatic control panels in the residential sector. They are also available, upon request, with various engine options, including Cummins, Volvo, Deutz, and Mitsubishi.

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 52.8

Maximum power three phase (KVA): 66

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: HONDA GC160

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 3300

Number cylinders: 3





Cooling: Water

Fuel tank capacity (L): 109

Consumption (L/h): 9.5

Running time (h): 11.4

Acoustic pressure: 67 dB(A) at 7 m

Length (mm): 2450

Width (mm): 1050

Height (mm): 1450

Dry weight (Kg): 1750

Silenced: No

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: No

Engine manufacturer: Perkins

