



# GREEN POWER GP18SH-PW-C - SOUNDPROOF

**Product price:**

**7.364,00 € tax excluded**

## **Product description:**

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

## **You can choose from several versions:**

- Silenced group with Compound-Linz alternator (automatic control pack)
- Silenced group with AVR-Leroy alternator (automatic control pack)
  
- Silenced group with high AVR-Mecc alternator (automatic control unit)
  
- Silenced group with AVR-Stamford alternator (automatic control unit)

The image is purely indicative.

## **Product features:**

Phase: Three phase

Maximum power three phase (KW): 13.6

Continuous power three phase (KW): 12

Maximum power three phase (KVA): 17





Continuous power three phase (KVA): 15  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: Presa 32A 5P  
Engine: PERKINS 403A-15G2  
Emissions Regulations: NON EMISSIONATO  
Engine rpm (rpm): 1500  
Speed governor: Mechanical  
Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 1496  
Number cylinders: 3  
Cylinders' position: In line  
Cooling: Water  
Alternator: Linz E1S13ME/4, synchronous, with brushes  
Poles: 4  
Fuel tank capacity (L): 70  
Acoustic pressure: 70 dB(A) at 7 m  
Length (mm): 1750  
Width (mm): 700  
Height (mm): 1020  
Dry weight (Kg): 560  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : Optional  
Voltage regulator: Compound / AVR (optional)

