



---

# TECNOGEN SH180E

## Product description:

TECNOGEN SH180E MOTORWELDING 4,5KVA

TECNOGEN SH180E features a rugged frame to protect a powerful HONDA GX270 motor capable of delivering 4.5KVA single-phase power with a maximum load consumption of 2.4 L/h.

TECNOGEN SH180E is with electric start with 12V battery supplied with acid or manual with self-winding, with control panel QM115 composed of singlephase CEE socket 2P+T 16A, thermal protection, singlephase Schuko socket 2P+T 16A.

## TECHNICAL FEATURES TECNOGEN SH180E

Soldering at 60%: 170

Maximum single-phase power: 4.5 KVA

Fuel: Gasoline

Voltage: 230V

Engine: Honda GX270

Boosting: Electric

Length: 780 mm

Width: 520 mm

Height: 560 mm

Weight: 80 Kg

Are you looking for a motorwelding with different technical characteristics? Here you can find the full range of TECNOGEN and other specialized brands.

The images are purely indicative.

## Product features:

Phase: Single phase

Maximum power single phase (KVA): 4.5

Fuel: Gasoline





Frequency (Hz): 50  
Voltage (V): 230  
Engine: HONDA GC160  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 160  
Number cylinders: 1  
Cooling: Air  
Welding current (A): 180 al 35% - 170 al 60%  
Fuel tank capacity (L): 2  
Consumption (L/h): 0,8 al 75% del carico  
Running time (h): 2,5  
Acoustic power: 95 dB(A)  
Length (mm): 78  
Width (mm): 52  
Height (mm): 56  
Dry weight (Kg): 27  
Inverter: No  
AVR: No  
Compound: No  
Silenced: Yes  
Super silenced: No

